



UniFi Access API Documentation

Leverage the power of the UniFi Access API



1. Introduction	2
1.1 Create API Token & Download API Documentation	2
1.2 Obtain Your Hostname	2
1.3 Use the API	2
1.4 Security Configuration	2
1.5 Important Notes	3
2. Overview	4
2.1 API Token	4
2.2 HTTP Status Code Reference	4
2.3 Success Code	4
2.4 Error Code	4
2.5 HTTP Verbs	6
2.6 API Host	6
2.7 Request Header	6
2.8 Response Schema	6
3. User	8
3.1 Schemas	8
3.2 User Registration	8
3.3 Update User	10
3.4 Fetch User	11
3.5 Fetch All Users	13
3.6 Assign Access Policy to User	15
3.7 Assign NFC Card to User	17
3.8 Unassign NFC Card from User	18
3.9 Assign PIN Code to User	19
3.10 Unassign PIN Code from User	20
4. Visitor	22
4.1 Schemas	22
4.2 Create Visitor	22
4.3 Fetch Visitor	26
4.4 Fetch All Visitors	28
4.5 Update Visitor	29

4.6 Delete Visitor	33
4.7 Assign NFC Card To Visitor	34
4.8 Unassign NFC Card From Visitor	35
4.9 Assign PIN Code To Visitor	36
4.10 Unassign PIN Code From Visitor	37
5. Access Policy	39
5.1 Access Policy Schemas	39
5.2 Create Access Policy	39
5.3 Update Access Policy	41
5.4 Delete Access Policy	43
5.5 Fetch Access Policy	44
5.6 Fetch All Access Policies	45
5.7 Holiday Group Schemas	47
5.8 Create Holiday Group	47
5.9 Update Holiday Group	50
5.10 Delete Holiday Group	52
5.11 Fetch Holiday Group	53
5.12 Fetch All Holiday Groups	54
5.13 Schedule Schemas	56
5.14 Create Schedule	57
5.15 Update Schedule	61
5.16 Fetch Schedule	63
5.17 Fetch All Schedules	65
5.18 Delete Schedule	67
6. Credential	68
6.1 Generate PIN Code	68
6.2 Enroll NFC Card	69
6.3 Fetch NFC Card Enrollment Status	70
6.4 Remove a Session Created for NFC Card Enrollment	71
7. Space	72
7.1 Fetch Door Group Topology	72
7.2 Create Door Group	74
7.3 Fetch Door Group	75

7.4 Update Door Group	78
7.5 Fetch All Door Groups	80
7.6 Delete Door Group	82
7.7 Fetch Door	83
7.8 Fetch All Doors	84
7.9 Remote Door Unlocking	86
8. Device	88
8.1 Fetch Devices	88
9. System Log	90
9.1 Topic Reference	90
9.2 Fetch System Logs	90

1. Introduction

Welcome to the UniFi Access API guide, which provides a detailed step-by-step explanation of how to utilize the API effectively. The UniFi Access API is an open interface protocol that allows developers to interact with a specific service using predefined interfaces.

1.1 Create API Token & Download API Documentation

Before you can use the UniFi Access API, you need to obtain a valid API Token for authentication and access control. Follow the steps below to create an API Token:

1. Sign in to your UniFi Portal (<https://account.ui.com/login>) using your web browser.
2. Select the UniFi Console where the UniFi Access application is installed.
3. Go to **Applications > Access > Settings > Security > Advanced**.
4. Go to **API Token** to **Download API documentation** and create an API Token.
5. To create an API Token, click **Create New**, enter the key name and validity period, select the permission scopes, and click **Create**.
6. Once the API Token is created, ensure to **Copy API Token** and store it safely for future use. Please note that the key is displayed only once for security purposes.

1.2 Obtain Your Hostname

The UniFi Access application can be hosted on a server within the local network and accessed via the LAN port. The hostname can either be the server's IP address or a custom domain name mapped to that IP. Connect using the specified port number (**12445**) and establish an HTTPS protocol for a secure connection.

1.3 Use the API

1. Construct the API request as per the instructions in the API documentation.
2. Send the constructed request to the server using the previously obtained API Token and hostname.
3. Parse the server's response to retrieve the required data or perform desired operations.

1.4 Security Configuration

1. Set up appropriate security measures to protect the API and the server.
2. Configure firewall rules to allow incoming traffic on the specific ports used by the API.
3. Enable HTTPS encryption using SSL/TLS certificates to secure data transmission.
4. Implement rate limiting and throttling mechanisms to prevent abuse and ensure fair usage.

1.5 Important Notes

1. Ensure your UniFi Access version is **1.9.1** or later.
2. **The API is not available after upgrading to Identity Enterprise.**
3. Obtain valid access permissions and adhere to the usage guidelines provided by the service provider before using the UniFi Access API.
4. Safeguard your API Token and do not share it with others to avoid security risks.
5. If you have any questions or concerns, please contact the technical support team of your service provider.

The steps above cover the basic process and essential considerations for using the UniFi Access API. Follow the instructions and refer to the API documentation for smooth development. Enjoy the convenience of using the UniFi Access API!

2. Overview

This section provides an introduction to essential concepts related to working with APIs, including API tokens, HTTP status codes, success and error codes, HTTP verbs, and API hosts.

2.1 API Token

To authenticate API requests with UniFi Access, you need to utilize API tokens associated with your account. If a request includes a deleted or expired token, the service will return an authentication error. The **Authorization Token** is obtained from UniFi Portal.

2.2 HTTP Status Code Reference

200	OK	Everything worked as expected.
400	Bad Request	The request is unacceptable, often due to missing required parameters.
401	Unauthorized	The request lacks a valid API token for authentication.
402	Request Failed	The request contains valid parameters, but failed for some reason.
403	Forbidden	The API token used does not have the necessary permissions to perform the request.
429	Too Many Requests	Too many requests were sent to the API in a short amount of time.
500, 502, 503, 504	Server Errors	Something went wrong on UniFi Access's end during request processing.

2.3 Success Code

```
{"code": "SUCCESS", "msg": "success"}
```

Code	Message
SUCCESS	Success

2.4 Error Code

```
{"code": "CODE_PARAMS_INVALID", "msg": "Invalid parameters."}
```

Code	Message
CODE_PARAMS_INVALID	The provided parameters are invalid.
CODE_SYSTEM_ERROR	An error occurred on the server's end.
CODE_RESOURCE_NOT_FOUND	The requested resource was not found.
CODE_OPERATION_FORBIDDEN	The requested operation is not allowed.
CODE_AUTH_FAILED	Authentication failed.
CODE_ACCESS_TOKEN_INVALID	The provided access token is invalid.
CODE_UNAUTHORIZED	You not are allowed to perform this action.
CODE_NOT_EXISTS	The requested item does not exist.
CODE_USER_EMAIL_ERROR	The provided email format is invalid.
CODE_USER_ACCOUNT_NOT_EXIST	The requested user account does not exist.
CODE_USER_WORKER_NOT_EXISTS	The requested user does not exist.
CODE_USER_NAME_DUPLICATED	The provided name already exists.
CODE_USER_CSV_IMPORT_INCOMPLETE_PROP	Please provide both first name and last name.
CODE_ACCESS_POLICY_USER_TIMEZONE_NOT_FOUND	The requested workday schedule could not be found.
CODE_ACCESS_POLICY_HOLIDAY_TIMEZONE_NOT_FOUND	The requested holiday schedule could not be found.
CODE_ACCESS_POLICY_HOLIDAY_GROUP_NOT_FOUND	The requested holiday group could not be found.
CODE_ACCESS_POLICY_HOLIDAY_NOT_FOUND	The requested holiday could not be found.
CODE_ACCESS_POLICY_SCHEDULE_NOT_FOUND	The requested schedule could not be found.
CODE_ACCESS_POLICY_HOLIDAY_NAME_EXIST	The provided holiday name already exists.
CODE_ACCESS_POLICY_HOLIDAY_GROUP_NAME_EXIST	The provided holiday group name already exists.
CODE_ACCESS_POLICY_SCHEDULE_NAME_EXIST	The provided schedule name already exists.
CODE_ACCESS_POLICY_SCHEDULE_CAN_NOT_DELETE	The schedule could not be deleted.
CODE_ACCESS_POLICY_HOLIDAY_GROUP_CAN_NOT_DELETE	The holiday group could not be deleted.
CODE_CREDS_NFC_HAS_BIND_USER	The NFC card is already registered and assigned to another user.
CODE_CREDS_DISABLE_TRANSFER_UID_USER_NFC	The UniFi Identity Enterprise user's NFC card is not transferrable.
CODE_CREDS_NFC_READ_SESSION_NOT_FOUND	Failed to obtain the NFC read session.
CODE_CREDS_NFC_READ_POLL_TOKEN_EMPTY	The NFC token is empty.
CODE_CREDS_NFC_CARD_IS_PROVISION	The NFC card is already registered at another site.
CODE_CREDS_NFC_CARD_PROVISION_FAILED	Please hold the NFC card against the reader for more than 5 seconds.
CODE_CREDS_NFC_CARD_INVALID	The card type is not supported. Please use a UA Card.
CODE_CREDS_NFC_CARD_CANNOT_BE_DELETE	The NFC card could not be deleted.
CODE_CREDS_PIN_CODE_CREDS_ALREADY_EXIST	The PIN code already exists.
CODE_CREDS_PIN_CODE_CREDS_LENGTH_INVALID	The PIN code length does not meet the preset requirements.
CODE_SPACE_DEVICE_BOUND_LOCATION_NOT_FOUND	The device's location was not found.
CODE_DEVICE_DEVICE_VERSION_NOT_FOUND	The firmware version is up to date.

CODE_DEVICE_DEVICE_VERSION_TOO_OLD	The firmware version is too old. Please update to the latest version.
CODE_DEVICE_DEVICE_BUSY	The camera is currently in use.
CODE_DEVICE_DEVICE_NOT_FOUND	The device was not found.
CODE_DEVICE_DEVICE_OFFLINE	The device is currently offline.
CODE_OTHERS_UID_ADOPTED_NOT_SUPPORTED	The API is not available after upgrading to Identity Enterprise.
CODE_HOLIDAY_GROUP_CAN_NOT_DELETE	The holiday group could not be deleted.
CODE_HOLIDAY_GROUP_CAN_NOT_EDIT	The holiday group could not be edited.

2.5 HTTP Verbs

HTTP Method	Description
GET	Used for retrieving objects.
POST	Used for creating objects or performing custom actions.
PUT	Used for replacing objects or collections.
DELETE	Used for deleting objects.

2.6 API Host

The Open API Server is hosted on port 12445 and can be accessed via HTTPS at <https://console-ip:12445>. The server certificate is self-generated and untrusted.

2.7 Request Header

The header for a request contains the following information:

Parameter	Required	Type	Description	Example
Authorization	T	String	Token required for authentication and access control.	Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg

2.8 Response Schema

The response for a request contains the following information:

```
{
  "code": "SUCCESS",
  "msg": "success",
  "data": {}
}
```

}

1. code: Represents the result of request handling and indicates success or failure.
2. msg: Represents the error description if the code is not equal to 1.
3. data: Represents the data of API requests.

3. User

The APIs here are designed for managing users, including handling their basic information and assigning NFC cards, PIN codes, and access policies to them.

3.1 Schemas

Parameter	Type	Description
Id	String	Identity ID of the user.
first_name	String	First name of the user.
last_name	String	Last name of the user.
employee_number	String	Employee number of the user.
onboard_time	Integer	User onboarding date.
nfc_cards	Array[Object]	Token associated with the bound NFC card.
nfc_cards[].id	String	Display ID of the NFC card.
nfc_cards[].token	String	Unique NFC card token.
pin_code	Object	Token associated with the bound PIN code.
pin_code.token	String	The user's PIN hash code credential for unlocking a door.
access_policy_ids	Array[String]	Collection of the access policy ID.
access_policies	Array[Object]	All policies assigned to the user.
status	String	<code>enum status {ACTIVE,PENDING,DEACTIVATED}</code> ACTIVE: The user account is in active status. PENDING: A new admin account has been invited by the SSO account, but the invitation has not been accepted. DEACTIVATED: The account has been deactivated.

3.2 User Registration

This API allows you to register a new user.

- Request URL: `/api/v1/developer/users`
- Permission Key: `edit:user`
- Method: `POST`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Body

Parameter	Required	Type	Description	Example	How to Get It?
first_name	T	String	First name of the user.		
last_name	T	String	Last name of the user.		
employee_number	F	String	Employee number of the user. Omit this parameter if it doesn't need to be updated.		
onboard_time	F	Integer	User onboarding date.	1689150139	

Response Body

Schemas: [Schemas](#)

Response Sample

```
1 {
2   "code": "SUCCESS",
3   "msg": "success",
4   "data": {
5     "first_name": "Fist Name",
6     "last_name": "Last Name",
7     "id": "37f2b996-c2c5-487b-aa22-8b453ff14a4b"
8   }
9 }
```

Request Sample

The request body should be a JSON object containing the following fields:

```
1 curl '{{host}}/api/v1/developer/users'
2   -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3   -H 'accept: application/json'
4   -H 'content-type: application/json'
5   --data-raw '{
6     "first_name": "H",
7     "last_name": "L",
8     "employee_number": "100000",
9     "onboard_time": 1689150139
10  }'
```

3.3 Update User

This API allows you to update user details.

- Request URL: `/api/v1/developer/users/:id`
- Permission Key: `edit:user`
- Method: `PUT`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description	Example
id	T	String	Identity ID of the user.	348e868e-534a-4ace-ba77-ce80394e31e3

Request Body

Parameter	Required	Type	Description	Example	How to Get It?
first_name	F	String	First name of the user.		
last_name	F	String	Last name of the user.		
employee_number	F	String	Employee number of the user.		
onboard_time	F	Integer	User onboarding date.	1689150139	

Response Body

Schemas: [Schemas](#)

Response Sample

```

1  {
2    "code": "SUCCESS",
3    "data": {
4      "employee_number": "10000000",
5      "first_name": "H",
6      "id": "f4fcdf85-2960-4888-8bfd-8232b736579b",
7      "last_name": "L",
8      "onboard_time": 1689150139,
9      "status": "ACTIVE"
10   },
11   "msg": "success"
12 }

```

Request Sample

The request body should be a JSON object containing the following fields:

```

1  curl -XPUT '{{host}}/api/v1/developer/user'
2    -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3    -H 'accept: application/json'
4    -H 'content-type: application/json'
5    --data-raw '{
6      "first_name": "H",
7      "last_name": "L",
8      "employee_number": "",
9      "pin_code": "",
10     "onboard_time": 1689150139
11   }'

```

3.4 Fetch User

This API allows you to fetch user details.

- Request URL: `/api/v1/developer/users/:id`
- Permission Key: `view:user`
- Method: `GET`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description	Example
id	T	String	Identity ID of the user.	348e868e-534a-4ace-ba77-ce80394e31e3

Query Parameters

Parameter	Required	Type	Description	Example
expand[]	F	Boolean	Determine whether to return the access policies assigned to a user (Optional).	expand[]=access_policy

Response Body

Schemas: [Schemas](#)

Response Sample

```
1  {
2    "code": "SUCCESS",
3    "data": {
4      "access_policies": [
5        {
6          "id": "edbc80df-3698-49fd-8b53-f1867f104947",
7          "name": "test",
8          "resources": [
9            {
10             "id": "d5573467-d6b3-4e8f-8e48-8a322b91664a",
11             "type": "door_group"
12           },
13           {
14             "id": "5c496423-6d25-4e4f-8cdf-95ad5135188a",
15             "type": "door_group"
16           },
17           {
18             "id": "6ff875d2-af87-470b-9cb5-774c6596afc8",
19             "type": "door"
20           }
21         ],
22         "schedule_id": "73facd6c-839e-4521-a4f4-c07e1d44e748"
23       }
24     ],
25     "access_policy_ids": [
26       "edbc80df-3698-49fd-8b53-f1867f104947"
27     ],
28     "employee_number": "",
29     "first_name": "***",
30     "id": "17d2f099-99df-429b-becb-1399a6937e5a",
```

```

31     "last_name": "L",
32     "nfc_cards": [
33         {
34             "id": "100001",
35             "token":
36             "d27822fc682b478dc637c6db01813e465174df6e54ca515d8427db623cfda1d0",
37             "type": "ua_card"
38         }
39     ],
40     "onboard_time": 1689047588,
41     "pin_code": {
42         "token":
43         "5f742ee4424e5a7dd265de3461009b9ebafa1fb9d6b15018842055cc0466ac56"
44     },
45     "status": "ACTIVE"
46 }

```

Request Sample

The request body should be a JSON object containing the following fields:

```

1 curl -XGET '{{host}}/api/v1/developer/users/348e868e-534a-4ace-ba77-ce80394e31e3?
   expand[]=access_policy'
2     -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3     -H 'accept: application/json'
4     -H 'content-type: application/json'

```

3.5 Fetch All Users

This API allows you to fetch all users.

- Request URL: `/api/v1/developer/users`
- Permission Key: `view:user`
- Method: `GET`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Query Parameters

Parameter	Required	Type	Description	Example
expand[]	F	Boolean	Determine whether to return the access policies assigned to a user (Optional).	expand[]=access_policy
page_num	F	String	Current page number in the pagination.	1
page_size	F	String	Number of users per page.	25

Response Body

Schemas: [Schemas](#)

Response Sample

```
1  {
2    "code": "SUCCESS",
3    "data": [
4      {
5        "access_policies": [
6          {
7            "id": "73f15cab-c725-4a76-a419-a4026d131e96",
8            "name": "Default Admin Policy",
9            "resources": [
10             {
11               "id": "d5573467-d6b3-4e8f-8e48-8a322b91664a",
12               "type": "door_group"
13             },
14             {
15               "id": "5c496423-6d25-4e4f-8cdf-95ad5135188a",
16               "type": "door_group"
17             }
18           ],
19           "schedule_id": "73facd6c-839e-4521-a4f4-c07e1d44e748"
20         }
21       ],
22       "access_policy_ids": [
23         "73f15cab-c725-4a76-a419-a4026d131e96"
24       ],
25       "employee_number": "",
26       "first_name": "UniFi",
27       "id": "83569f9b-0096-48ab-b2e4-5c9a598568a8",
28       "last_name": "User",
29       "nfc_cards": [],
30       "onboard_time": 0,
31       "pin_code": null,
32       "status": "ACTIVE"
33     },
```

```

34     {
35         "access_policies": [
36             {
37                 "id": "c1682fb8-ef6e-4fe2-aa8a-b6f29df753ff",
38                 "name": "policy_1690272668035",
39                 "resources": [
40                     {
41                         "id": "6ff875d2-af87-470b-9cb5-774c6596afc8",
42                         "type": "door"
43                     }
44                 ],
45                 "schedule_id": "0616ef06-b807-4372-9ae0-7a87e12e4019"
46             }
47         ],
48         "access_policy_ids": [
49             "c1682fb8-ef6e-4fe2-aa8a-b6f29df753ff"
50         ],
51         "employee_number": "",
52         "first_name": "Ttttt",
53         "id": "3a3ba57a-796e-46e0-b8f3-478bb70a114d",
54         "last_name": "Tttt",
55         "nfc_cards": [],
56         "onboard_time": 1689048000,
57         "pin_code": null,
58         "status": "ACTIVE"
59     }
60 ],
61 "msg": "success",
62 "pagination": {
63     "page_num": 1,
64     "page_size": 97,
65     "total": 97
66 }
67 }

```

Request Sample

The request body should be a JSON object containing the following fields:

```

1  curl -XGET '{{host}}/api/v1/developer/users?
    page_num=1&page_size=25&expand[]=access_policy'
2      -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3      -H 'accept: application/json'
4      -H 'content-type: application/json'

```

3.6 Assign Access Policy to User

- Request URL: `/api/v1/developer/users/:id/access_policies`
- Permission Key: `edit:user`
- Method: `PUT`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description	How to Get It?
id	T	String	Identity ID of the user.	Get it from the API <code>/api/v1/developer/users</code>

Request Body

Parameter	Required	Type	Description	How to Get It?
access_policy_ids	T	Array[String]	Collection of multiple policy IDs.	Get it from the API <code>/api/v1/developer/access_policies</code>

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```

1 //assign access policies to user
2 curl -XPUT '{{host}}/api/v1/developer/users/38857332-7a5e-4bb6-8837-
  651b2a47cea5/access_policies'
3     -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
4     -H 'accept: application/json'
5     -H 'content-type: application/json'
6     --data-raw '{
7         "access_policy_ids": [
8             "03895c7f-9f53-4334-812b-5db9c122c109",
9             "3b6bcb0c-7498-44cf-8615-00a96d824cbe"
10        ]
11    }'
12
13 //remove all access policies from user
14 curl -XPUT '{{host}}/api/v1/developer/users/38857332-7a5e-4bb6-8837-
  651b2a47cea5/access_policies'
15     -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
16     -H 'accept: application/json'
17     -H 'content-type: application/json'
18     --data-raw '{

```

```
19 |     "access_policy_ids": []
20 |   }'
```

Response Sample

```
1 | { "code": "SUCCESS", "msg": "success" }
```

3.7 Assign NFC Card to User

- Request URL: `/api/v1/developer/users/:id/nfc_cards`
- Permission Key: `edit:user`
- Method: `PUT`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description	How to Get It?
id	T	String	Identity ID of the user.	Get it from the API <code>/api/v1/developer/users</code>

Request Body

Parameter	Required	Type	Description	How to Get It?
token	T	String	Token of the NFC card.	Get it from the API <code>/api/v1/developer/nfc_cards/sessions/{session_id}</code>
force_add	F	Boolean	Determine whether to overwrite an NFC card that has already been assigned.	true or false

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```

1 curl -XPUT '{{host}}/api/v1/developer/users/17d2f099-99df-429b-becb-
1399a6937e5a/nfc_cards
2     -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3     -H 'accept: application/json'
4     -H 'content-type: application/json'
5     --data-raw '{
6         "token": "d27822fc682b478dc637c6db01813e465174df6e54ca515d8427db623cfda1d0",
7         "force_add": true
8     }'
9

```

Response Sample

```

1 { "code": "SUCCESS", "msg": "success" }

```

3.8 Unassign NFC Card from User

- Request URL: `/api/v1/developer/users/:id/nfc_cards/delete`
- Permission Key: `edit:user`
- Method: `PUT`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description	How to Get It?
id	T	String	Identity ID of the user.	Get it from the API <code>/api/v1/developer/users</code>

Request Body

Parameter	Required	Type	Description	How to Get It?
token	T	String	Token of the NFC card.	Get it from the API <code>/api/v1/developer/users</code>

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```
1 curl -XDELETE '{{host}}/api/v1/developer/users/17d2f099-99df-429b-becb-
2     1399a6937e5a/nfc_cards/delete
3     -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
4     -H 'accept: application/json'
5     -H 'content-type: application/json'
6     -d '{
7         "token": "d27822fc682b478dc637c6db01813e465174df6e54ca515d8427db623cfda1d0"
8     }'
```

Response Sample

```
1 { "code": "SUCCESS", "msg": "success" }
```

3.9 Assign PIN Code to User

- Request URL: `/api/v1/developer/users/:id/pin_codes`
- Permission Key: `edit:user`
- Method: `PUT`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description	How to Get It?
id	T	String	Identity ID of the user.	Get it from the API <code>/api/v1/developer/users</code>

Request Body

Parameter	Required	Type	Description	How to Get It?
pin_code	T	String	Generate a PIN code for the user to unlock doors.	Get it from the API <code>/api/v1/developer/pin_codes</code>

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```
1 curl -XPUT '{{host}}/api/v1/developer/users/17d2f099-99df-429b-becb-
  1399a6937e5a/pin_codes
2     -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3     -H 'accept: application/json'
4     -H 'content-type: application/json'
5     --data-raw '{
6         "pin_code": "57301208"
7     }'
```

Response Sample

```
1 { "code": "SUCCESS", "msg": "success" }
```

3.10 Unassign PIN Code from User

- Request URL: `/api/v1/developer/users/:id/pin_codes`
- Permission Key: `edit:user`
- Method: `DELETE`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description	How to Get It?
id	T	String	Identity ID of the user.	Get it from the API <code>/api/v1/developer/users</code>

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```
1 curl -XDELETE '{{host}}/api/v1/developer/users/17d2f099-99df-429b-becb-  
1399a6937e5a/pin_codes  
2     -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'  
3     -H 'accept: application/json'  
4     -H 'content-type: application/json'  
5
```

Response Sample

```
1 { "code": "SUCCESS", "msg": "success" }
```


4. Visitor

The APIs here are designed for managing visitors, including creating, viewing, and deleting visitors. They also enable the assigning of NFC cards, schedules, PIN codes, locations, and other access resources to visitors.

4.1 Schemas

Parameter	Type	Description
id	String	Identity ID of the visitor.
first_name	String	First name of the visitor.
last_name	String	Last name of the visitor.
status	String	The visitor's status. <code>enum status</code> {UPCOMING=1,VISITED=2,visitor=3,CANCELLED=4,NO_VISIT=5,ACTIVE=6}
nfc_cards	Array[Object]	Token associated with the bound NFC card.
nfc_cards[].id	String	Display ID of the NFC card.
nfc_cards[].token	String	Unique NFC card token.
pin_code	Object	Token associated with the bound PIN code.
pin_code.token	String	The user's PIN hash code credential for unlocking a door.
schedule_id	String	Identity ID of the schedule.
schedule	Object	The schedule assigned to the visitor.
schedule.name	String	Name of the schedule.
schedule.type	String	Type of the schedule.
schedule.week_schedule	Object	The customizable scheduling strategy for each day from Sunday to Saturday. If not specified, it means access is allowed every day.
schedule.week_schedule.monday	Array[Object]	Specify the daily access time period from Sunday to Saturday.
schedule.week_schedule.monday[0].start_time	String	Start time of the access time period.
schedule.week_schedule.monday[0].end_time	String	End time of the access time period.
resources	Array[Object]	Specify the locations that the visitor can access.
resources[0].id	String	Identity ID of the door group.
resources[0].name	String	Name of the door group.
resources[0].type	String	Type of the door group.

4.2 Create Visitor

This API enables you to create a new visitor.

- Request URL: `/api/v1/developer/visitors`
- Permission Key: `edit:visitor`
- Method: `POST`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Body

Parameter	Required	Type	Description	Example	How to Get It?
first_name	T	String	First name of the visitor.		
last_name	T	String	Last name of the visitor.		
remarks	F	String	Remarks about the visitor.		
mobile_phone	F	String	Mobile phone number of the visitor.		
email	F	String	Email address of the visitor.		
visitor_company	F	String	Company name of the visitor.		
start_time	T	Integer	Start time of the visit.	1688546460	
end_time	T	Integer	End time of the visit.	1688572799	
visit_reason	T	String	Visit reason: <code>enum reason</code> {Interview,Business,Cooperation,Others}	Interview	

Assign Available Locations to Visitor

Parameter	Required	Type	Description	Example	How to Get It?
resources	F	Array[Object]	Assign available locations to the visitor.		Get it from the API <code>/api/v1/developer/door_groups/topology</code>
resources[0].id	F	String	When resource type is <code>door_group</code> , it refers to the group ID of a building or a customized door group. When type is <code>door</code> , it refers to the ID of a door.	9bee6e0e-108d-4c52-9107-76f2c7dea4f1	
resources[0].type	F	String	Support both <code>door</code> and <code>door_group</code> .	door_group	

Assigned Schedules To Visitor

Parameter	Required	Type	Description	Example
week_schedule	F	Object	The customizable scheduling strategy for each day from Sunday to Saturday. If not specified, it means access is allowed every day.	
week_schedule.monday	F	Array[Object]	Specify the daily access time period from Sunday to Saturday.	
week_schedule.monday[0].start_time	F	String	Start time of the access time period.	00:00:00
week_schedule.monday[0].end_time	F	String	End time of the access time period.	23:59:59

Response Body

Schemas: [Schemas](#)

Response Sample

```
1  {
2    "code": "SUCCESS",
3    "data": {
4      "first_name": "H",
5      "id": "fbe8d920-47d3-4cfd-bda7-bf4b0e26f73c",
6      "last_name": "L",
7      "nfc_cards": [],
8      "resources": [
9        {
10         "id": "5c496423-6d25-4e4f-8cdf-95ad5135188a",
11         "name": "Test Group",
12         "type": "door_group"
13       },
14       {
15         "id": "d5573467-d6b3-4e8f-8e48-8a322b91664a",
16         "name": "UNVR",
17         "type": "door_group"
18       },
19       {
20         "id": "369215b0-cabe-49b6-aeaa-e0b7ec6424d5",
21         "name": "visitor-1691671529285",
22         "type": "door_group"
23       }
24     ],
25     "schedule": {
26       "id": "1fb849bb-e7e5-4516-8dd9-b78094a6708a",
27       "is_default": false,
28       "name": "schedule-1691671529237",
29       "type": "access",
30       "weekly": {
31         "friday": [
32           {
33             "end_time": "17:00:59",
34             "start_time": "10:00:00"
35           }
36         ],
37         "monday": [],
38         "saturday": [],
39         "sunday": [],
40         "thursday": [
41           {
42             "end_time": "17:00:59",
43             "start_time": "11:00:00"
```

```

44         }
45     ],
46     "tuesday": [
47         {
48             "end_time": "17:00:59",
49             "start_time": "10:00:00"
50         }
51     ],
52     "wednesday": [
53         {
54             "end_time": "17:00:59",
55             "start_time": "10:00:00"
56         }
57     ]
58 }
59 },
60 "schedule_id": "1fb849bb-e7e5-4516-8dd9-b78094a6708a",
61 "status": "ACTIVE"
62 },
63 "msg": "success"
64 }

```

Request Sample

The request body should be a JSON object containing the following fields:

```

1  curl 'http://127.0.0.1:12080/api/v1/developer/visitors'
2      -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3      -H 'accept: application/json'
4      -H 'content-type: application/json' --data-raw
5  {
6      "first_name": "H",
7      "last_name": "L",
8      "remarks": "",
9      "mobile_phone": "",
10     "email": "",
11     "visitor_company": "",
12     "start_time": 1688546460,
13     "end_time": 1788572799,
14     "visit_reason": "Interview",
15     "week_schedule": {
16         "sunday": [],
17         "monday": [],
18         "tuesday": [
19             {
20                 "start_time": "10:00:00",
21                 "end_time": "17:00:59"
22             }
23         ],

```

```

24     "wednesday": [
25         {
26             "start_time": "10:00:00",
27             "end_time": "17:00:59"
28         }
29     ],
30     "thursday": [
31         {
32             "start_time": "11:00:00",
33             "end_time": "17:00:59"
34         }
35     ],
36     "friday": [
37         {
38             "start_time": "10:00:00",
39             "end_time": "17:00:59"
40         }
41     ],
42     "saturday": []
43 },
44 "resources": [
45     {
46         "id": "6ff875d2-af87-470b-9cb5-774c6596afc8",
47         "type": "door"
48     },
49     {
50         "id": "5c496423-6d25-4e4f-8cdf-95ad5135188a",
51         "type": "door_group"
52     },
53     {
54         "id": "d5573467-d6b3-4e8f-8e48-8a322b91664a",
55         "type": "door_group"
56     }
57 ]
58 }

```

4.3 Fetch Visitor

This API enables you to fetch visitor details.

- Request URL: `/api/v1/developer/visitors/:id`
- Permission Key: `view:visitor`
- Method: `GET`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description
id	T	String	Identity ID of the visitor.

Response Body

Schemas: [Schemas](#)

Response Sample

```
1  {
2    "code": "SUCCESS",
3    "data": {
4      "first_name": "Hong+243",
5      "id": "3566867c-fa04-4752-98f6-43cf9a342d4a",
6      "last_name": "Lu",
7      "nfc_cards": [
8        {
9          "id": "100001",
10         "token":
11         "d27822fc682b478dc637c6db01813e465174df6e54ca515d8427db623cfda1d0",
12         "type": "ua_card"
13       }
14     ],
15     "pin_code": {
16       "token":
17       "bc3e3135013e2dcae119390b7897166e8cec3bcf5becb6b05578ab67634559ed"
18     },
19     "resources": [
20       {
21         "id": "fd293ecb-98d2-425b-a020-cb9365ea48b3",
22         "name": "visitor-1690337152955",
23         "type": "door_group"
24       }
25     ],
26     "schedule": {
27       "id": "6ccf9e1e-b174-476d-b2fe-96817c780fbf",
28       "is_default": false,
29       "name": "visitor-1690337152955",
```

```

28         "type": "access",
29         "weekly": null
30     },
31     "schedule_id": "6ccf9e1e-b174-476d-b2fe-96817c780fbf",
32     "status": "VISITED"
33 },
34 "msg": "success"
35 }

```

Request Sample

The request body should be a JSON object containing the following fields:

```

1 curl -XGET '{{host}}/api/v1/developer/visitors/76794bd8-98c0-49b6-9230-ba8c5812cf29'
2 -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3 -H 'accept: application/json'
4 -H 'content-type: application/json'

```

4.4 Fetch All Visitors

This API enables you to fetch the list of all visitors.

- Request URL: `/api/v1/developer/visitors`
- Permission Key: `view:visitor`
- Method: `GET`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Query Parameters

Parameter	Required	Type	Description	Example
status	F	Integer	The visitor's status. <code>enum status {UPCOMING=1, VISITED=2, visitor=3, CANCELLED=4, NO_VISIT=5, ACTIVE=6}</code>	1
keyword	F	String	Support prefix matching for first name and last name. NOTE: The status filtering is disabled when searching with keyword.	H
page_num	F	String	Current page number in the pagination.	1
page_size	F	String	Number of visitors per page.	25

Response Body

Schemas: [Schemas](#)

Request Sample

The request body should be a JSON object containing the following fields:

```
1 curl -XGET '{{host}}/api/v1/developer/visitors?page_num=1&page_size=25'  
2     -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'  
3     -H 'accept: application/json'  
4     -H 'content-type: application/json'  
5  
6 # fetch users through keyword  
7 curl -XGET '{{host}}/api/v1/developer/visitors?keyword=H'  
8     -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'  
9     -H 'accept: application/json'  
10    -H 'content-type: application/json'
```

4.5 Update Visitor

This API enables you to update a visitor.

- Request URL: `/api/v1/developer/visitors/:id`
- Permission Key: `edit:visitor`
- Method: `PUT`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Body

Parameter	Required	Type	Description	Example	How to Get It?
first_name	F	String	First name of the visitor.		
last_name	F	String	Last name of the visitor.		
remarks	F	String	Remarks about the visitor.		
mobile_phone	F	String	Mobile phone number of the visitor.		
email	F	String	Email address of the visitor.		
visitor_company	F	String	Company name of the visitor.		
start_time	F	Integer	Start time of the visit.	1688546460	
end_time	F	Integer	End time of the visit.	1688572799	
visit_reason	F	String	Visit reason: <code>enum reason</code> {Interview,Business,Cooperation,Others}	Interview	

Assign Available Locations to Visitor

Parameter	Required	Type	Description	Example	How to Get It?
resources	F	Array[Object]	Assign available locations to the visitor. Omit this parameter if it doesn't need to be updated.		Get it from the API <code>/api/v1/developer/door_groups/topology</code>
resources[0].id	F	String	When resource type is <code>door_group</code> , it refers to the group ID of a building or a customized door group. When type is <code>door</code> , it refers to the ID of a door.	9bee6e0e-108d-4c52-9107-76f2c7dea4f1	
resources[0].type	F	String	Support both <code>door</code> and <code>door_group</code> .		

Assigned Schedules To Visitor

Parameter	Required	Type	Description	Example
week_schedule	F	Object	The customizable scheduling strategy for each day from Sunday to Saturday. If not specified, it means access is allowed every day. Omit this parameter if it doesn't need to be updated.	
week_schedule.monday	F	Array[Object]	Specify the daily access time period from Sunday to Saturday.	
week_schedule.monday[0].start_time	F	String	Start time of the access time period.	00:00:00
week_schedule.monday[0].end_time	F	String	End time of the access time period.	23:59:59

Request Path

Parameter	Required	Type	Description
id	T	String	Identity ID of the visitor.

Response Body

Schemas: [Schemas]

Note: Status change is not supported.

Response Sample

```
1  {
2    "code": "SUCCESS",
3    "data": {
4      "first_name": "H",
5      "id": "8564ce90-76ba-445f-b78b-6cca39af0130",
6      "last_name": "L",
7      "nfc_cards": [],
8      "pin_code": null,
9      "resources": [
10     {
11       "id": "5c496423-6d25-4e4f-8cdf-95ad5135188a",
12       "name": "1111",
13       "type": "door_group"
14     },
15     {
16       "id": "d5573467-d6b3-4e8f-8e48-8a322b91664a",
17       "name": "UNVR",
18       "type": "door_group"
19     },
20     {
21       "id": "e311ca94-172c-49fe-9c91-49bd8ecef845",
22       "name": "visitor-1691646856144",
23       "type": "door_group"
24     }
25   ],
26   "schedule": {
27     "id": "c03bf601-0b90-4341-bce4-6061931e9f4e",
28     "is_default": false,
29     "name": "visitor-1691646856097",
30     "type": "access",
31     "weekly": {
32       "friday": [
33         {
34           "end_time": "17:00:59",
35           "start_time": "10:00:00"
36         }
37       ],
38       "monday": [
39         {
40           "end_time": "17:00:59",
41           "start_time": "10:00:00"
```

```

42         }
43     ],
44     "saturday": [],
45     "sunday": [],
46     "thursday": [
47         {
48             "end_time": "18:00:59",
49             "start_time": "11:00:00"
50         }
51     ],
52     "tuesday": [],
53     "wednesday": [
54         {
55             "end_time": "17:00:59",
56             "start_time": "10:00:00"
57         }
58     ]
59 }
60 },
61 "schedule_id": "c03bf601-0b90-4341-bce4-6061931e9f4e",
62 "status": "ACTIVE"
63 },
64 "msg": "success"
65 }

```

Request Sample

The request body should be a JSON object containing the following fields:

```

1  curl -XPUT '{{host}}/api/v1/developer/visitors/c81dfee6-5970-4938-bd30-
2  40820e16ea01'
3  -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
4  -H 'accept: application/json'
5  -H 'content-type: application/json'
6  --data-raw '
7  {
8  "first_name": "Test",
9  "last_name": "L",
10 "remarks": "",
11 "mobile_phone": "",
12 "email": "",
13 "visitor_company": "",
14 "start_time": 1688546460,
15 "end_time": 1788572799,
16 "visit_reason": "Interview",
17 "week_schedule": {
18     "sunday": [],
19     "monday": [

```

```

20         "start_time": "10:00:00",
21         "end_time": "17:00:59"
22     }
23 ],
24 "tuesday": [],
25 "wednesday": [
26     {
27         "start_time": "10:00:00",
28         "end_time": "17:00:59"
29     }
30 ],
31 "thursday": [
32     {
33         "start_time": "11:00:00",
34         "end_time": "18:00:59"
35     }
36 ],
37 "friday": [
38     {
39         "start_time": "10:00:00",
40         "end_time": "17:00:59"
41     }
42 ],
43 "saturday": []
44 },
45 "resources": [
46     {
47         "id": "6ff875d2-af87-470b-9cb5-774c6596afc8",
48         "type": "door"
49     },
50     {
51         "id": "5c496423-6d25-4e4f-8cdf-95ad5135188a",
52         "type": "door_group"
53     },
54     {
55         "id": "d5573467-d6b3-4e8f-8e48-8a322b91664a",
56         "type": "door_group"
57     }
58 ]
59 }
60 '

```

4.6 Delete Visitor

This API enables you to delete a visitor.

- Request URL: `/api/v1/developer/visitors/:id`

- Permission Key: `edit:visitor`
- Method: `DELETE`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description
id	T	String	Identity ID of the visitor.

Response Sample

```
1 {
2   "code": "SUCCESS",
3   "data": null,
4   "msg": "success"
5 }
```

Request Sample

The request body should be a JSON object containing the following fields:

```
1 curl -XDELETE 'http://127.0.0.1:12080/api/v1/developer/visitors/c81dfee6-5970-4938-
2   bd30-40820e16ea01'
3   -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
4   -H 'accept: application/json'
5   -H 'content-type: application/json'
```

4.7 Assign NFC Card To Visitor

- Request URL: `/api/v1/developer/visitors/:id/nfc_cards`
- Permission Key: `edit:visitor`
- Method: `PUT`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description	How to Get It?
id	T	String	Identity ID of the visitor.	Get it from the API <code>/api/v1/developer/visitors</code>

Request Body

Parameter	Required	Type	Description	How to Get It?
token	T	String	Token of the NFC card.	Get it from the API <code>/api/v1/developer/nfc_cards/sessions/{session_id}</code>
force_add	F	Boolean	Determine whether to overwrite an NFC card that has already been assigned.	true or false

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```
1 curl -XPUT '{{host}}/api/v1/developer/visitors/60b5c15e-9aff-4fc8-9547-  
d21d2e39c1ff/nfc_cards  
2     -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'  
3     -H 'accept: application/json'  
4     -H 'content-type: application/json'  
5     --data-raw '{  
6         "token": "d27822fc682b478dc637c6db01813e465174df6e54ca515d8427db623cfda1d0",  
7         "force_add": true  
8     }'  
9
```

Response Sample

```
1 { "code": "SUCCESS", "msg": "success" }
```

4.8 Unassign NFC Card From Visitor

- Request URL: `/api/v1/developer/visitors/:id/nfc_cards/delete`
- Permission Key: `edit:visitor`

- Method: `PUT`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description	How to Get It?
id	T	String	Identity ID of the visitor.	Get it from the API <code>/api/v1/developer/visitors</code>

Request Body

Parameter	Required	Type	Description	How to Get It?
token	T	String	Token of the NFC card.	Get it from the API <code>/api/v1/developer/visitors</code>

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```
1 curl -XPUT '{{host}}/api/v1/developer/visitors/60b5c15e-9aff-4fc8-9547-
   d21d2e39c1ff/nfc_cards/delete
2     -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3     -H 'accept: application/json'
4     -H 'content-type: application/json'
5     -d '{
6         "token": "d27822fc682b478dc637c6db01813e465174df6e54ca515d8427db623cfda1d0"
7     }'
```

Response Sample

```
1 { "code": "SUCCESS", "msg": "success" }
```

4.9 Assign PIN Code To Visitor

- Request URL: `/api/v1/developer/visitors/:id/pin_codes`
- Permission Key: `edit:visitor`
- Method: `PUT`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description	How to Get It?
id	T	String	Identity ID of the visitor.	Get it from the API <code>/api/v1/developer/visitors</code>

Request Body

Parameter	Required	Type	Description	How to Get It?
pin_code	T	String	Generate a PIN code for the visitor to unlock doors.	Get it from the API <code>/api/v1/developer/pin_codes</code>

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```
1 curl -XPUT '{{host}}/api/v1/developer/visitors/17d2f099-99df-429b-becb-
   1399a6937e5a/pin_codes
2     -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3     -H 'accept: application/json'
4     -H 'content-type: application/json'
5     --data-raw '{
6         "pin_code": "57301208"
7     }'
```

Response Sample

```
1 { "code": "SUCCESS", "msg": "success" }
```

4.10 Unassign PIN Code From Visitor

- Request URL: `/api/v1/developer/visitors/:id/pin_codes`
- Permission Key: `edit:visitor`
- Method: `DELETE`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description	How to Get It?
id	T	String	Identity ID of the visitor.	Get it from the API <code>/api/v1/developer/visitors</code>

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```
1 curl -XDELETE '{{host}}/api/v1/developer/visitors/17d2f099-99df-429b-becb-
   1399a6937e5a/pin_codes
2     -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3     -H 'accept: application/json'
4     -H 'content-type: application/json'
5
```

Response Sample

```
1 { "code": "SUCCESS", "msg": "success" }
```

5. Access Policy

The APIs here are designed for managing door access policies. These policies can be bound with access schedules, floors, and other door access resources.

5.1 Access Policy Schemas

Parameter	Type	Description
Id		Identity ID of the access policy.
name	String	Name of the access policy.
resources	Array[Object]	Specify the locations that can be accessed.
resources[].type	String	Include door and door_group resources. <code>enum type</code> {door,door_group}
resources[].id	String	When resource type is <code>door_group</code> , it refers to the group ID of a building or a customized door group. When type is <code>door</code> , it refers to the ID of a door.
schedule_id	String	Identity ID of the schedule.

5.2 Create Access Policy

This API allows you to create an access policy.

- Request URL: `/api/v1/developer/access_policies`
- Permission Key: `edit:policy`
- Method: `POST`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Body

Parameter	Required	Type	Description	How to Get It?	Example
name	T	String	Name of the access policy.		
resource	F	Array[Object]	Used to assign accessible locations to the access policy.	Get it from the API <code>/api/v1/developer/door_groups/topology;</code> <code>/api/v1/developer/door_groups</code>	
resources[].type	F	String	<code>enum type</code> <code>{door, door_group}</code>		
resources[].id	F	String	When resource type is <code>door_group</code> , it refers to the group ID of a building or a customized door group. When type is <code>door</code> , it refers to the ID of a door.		
schedule_id	T	String	Identity ID of the schedule. Assign additional schedules.	Get it from the API <code>/api/v1/developer/access_policies/schedules</code>	

Response Body

Parameter	Required	Type	Description	Related API	Purpose
id	T	String	Identity ID of the policy.	<code>/api/v1/developer/users/:user_id/access_policies</code>	Used to both assign an access policy to a user or unassign a policy from them.

Schemas: [Schemas](#)

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```

1  curl '{{host}}/api/v1/developer/access_policies'
2      -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3      -H 'accept: application/json'
4      -H 'content-type: application/json' --data-raw
5      '{
6          "name": "test",
7          "resource": [
8              {
9                  "id": "6ff875d2-af87-470b-9cb5-774c6596afc8",
10                 "type": "door"
11             },
12             {
13                 "id": "5c496423-6d25-4e4f-8cdf-95ad5135188a",
14                 "type": "door_group"
15             },
16             {
17                 "id": "d5573467-d6b3-4e8f-8e48-8a322b91664a",
18                 "type": "door_group"
19             }
20         ],
21         "schedule_id": "4e108aeb-ec9a-4822-bf86-170ea986f934"
22     }'
```

Response Sample

```
1 {
2   "code": "SUCCESS",
3   "data": {
4     "id": "bb5eb965-42dc-4206-9654-88a2d1c3aaa5",
5     "name": "test13",
6     "resources": [
7       {
8         "id": "6ff875d2-af87-470b-9cb5-774c6596afc8",
9         "type": "door"
10      },
11      {
12        "id": "5c496423-6d25-4e4f-8cdf-95ad5135188a",
13        "type": "door_group"
14      },
15      {
16        "id": "d5573467-d6b3-4e8f-8e48-8a322b91664a",
17        "type": "door_group"
18      }
19    ],
20    "schedule_id": "4e108aeb-ec9a-4822-bf86-170ea986f934"
21  },
22  "msg": "success"
23 }
```

5.3 Update Access Policy

This API allows you to update a policy.

- Request URL: `/api/v1/developer/access_policies/:id`
- Permission Key: `edit:policy`
- Method: `PUT`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description	Example
Id	T	String	Identity ID of the access policy.	

Request Body

Parameter	Required	Type	Description	How to Get It?
name	F	String	Name of the access policy. Omit this parameter if it doesn't need to be updated.	
resource	F	Array[Object]	Used to assign accessible locations to the access policy. Omit this parameter if it doesn't need to be updated.	Get it from the API <code>/api/v1/developer/door_groups/topology;</code> <code>/api/v1/developer/door_groups</code>
resources[].type	F	String	<code>enum type {door,door_group}</code>	
resources[].id	F	String	When resource type is <code>door_group</code> , it refers to the group ID of a building or a customized door group. When type is <code>door</code> , it refers to the ID of a door.	
schedule_id	F	String	Identity ID of the schedule. Assign additional schedules. Omit this parameter if it doesn't need to be updated.	Get it from the API <code>/api/v1/developer/access_policies/schedules</code>

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```
1 curl '{{host}}/api/v1/developer/access_policies/242c88e3-0524-42de-8447-45891c5df714'
2     -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3     -H 'accept: application/json'
4     -H 'content-type: application/json' --data-raw
5     '{
6         "name": "test",
7         "resource": [
8             {
9                 "id": "6ff875d2-af87-470b-9cb5-774c6596afc8",
10                "type": "door"
11            },
12            {
13                "id": "5c496423-6d25-4e4f-8cdf-95ad5135188a",
14                "type": "door_group"
15            },
16            {
17                "id": "d5573467-d6b3-4e8f-8e48-8a322b91664a",
18                "type": "door_group"
19            }
20        ],
21        "schedule_id": "4e108aeb-ec9a-4822-bf86-170ea986f934"
```

Response Body

Parameter	Required	Type	Description	Related api	Purpose
id	T	String	Identity ID of the policy.	<code>/api/v1/developer/users/:user_id/access_policies</code>	Used to both assign an access policy to a user or unassign a policy from them.

Schemas: [Schemas](#)

5.4 Delete Access Policy

This API allows you to delete an access policy.

- Request URL: `/api/v1/developer/access_policies/:id`
- Permission Key: `edit:policy`
- Method: `DELETE`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Body

Parameter	Required	Type	Description
Id	T	String	Identity ID of the access policy.

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```
1 curl -XDELETE '{{host}}/api/v1/developer/access_policies/460d0bcc-5d4f-4e7b-8a3c-8d4502765e11'
2     -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
```

Response Sample

```
1 { "code": "SUCCESS", "msg": "success", "data": "success" }
```

5.5 Fetch Access Policy

This API allows you to fetch a policy details.

- Request URL: `/api/v1/developer/access_policies/:id`
- Permission Key: `view:policy`
- Method: `GET`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Body

Parameter	Required	Type	Description
Id	T	String	Identity ID of the access policy.

Response Body

Parameter	Required	Type	Description	Example
Data	T	Object		

Schemas: [Schemas](#)

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```
1 curl '{{host}}/api/v1/developer/ccess_policy'  
2 -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'  
3 -H 'accept: application/json'  
4 -H 'content-type: application/json'
```

Response Sample

```
1 {  
2   "code": "SUCCESS",  
3   "data": {  
4     "id": "ed09985f-cf52-486e-bc33-377b6ed7bbf2",  
5     "name": "test11",  
6     "resources": [  
7
```

```

7      {
8          "id": "6ff875d2-af87-470b-9cb5-774c6596afc8",
9          "type": "door"
10     },
11     {
12         "id": "5c496423-6d25-4e4f-8cdf-95ad5135188a",
13         "type": "door_group"
14     },
15     {
16         "id": "d5573467-d6b3-4e8f-8e48-8a322b91664a",
17         "type": "door_group"
18     }
19 ],
20 "schedule_id": "4e108aeb-ec9a-4822-bf86-170ea986f934"
21 },
22 "msg": "success"
23 }

```

5.6 Fetch All Access Policies

This API allows you to fetch all access policies.

- Request URL: `/api/v1/developer/access_policies`
- Permission Key: `view:policy`
- Method: `GET`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Response Body

Parameter	Required	Type	Description	Example
Data	T	Array[Object]		

Schemas: [Schemas](#)

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:


```
1 curl '{{host}}/api/v1/developer/access_policies'
2   -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3   -H 'accept: application/json'
4   -H 'content-type: application/json'
```

Response Sample

```
1  {
2    "code": "SUCCESS",
3    "data": [
4      {
5        "id": "73f15cab-c725-4a76-a419-a4026d131e96",
6        "name": "Default Admin Policy",
7        "resources": [
8          {
9            "id": "d5573467-d6b3-4e8f-8e48-8a322b91664a",
10           "type": "door_group"
11         },
12         {
13           "id": "5c496423-6d25-4e4f-8cdf-95ad5135188a",
14           "type": "door_group"
15         }
16       ],
17       "schedule_id": "73facd6c-839e-4521-a4f4-c07e1d44e748"
18     },
19     {
20       "id": "b96948a4-fed9-40a3-9c4a-e473822a3db7",
21       "name": "Default UNVR Policy",
22       "resources": [
23         {
24           "id": "d5573467-d6b3-4e8f-8e48-8a322b91664a",
25           "type": "door_group"
26         },
27         {
28           "id": "6ff875d2-af87-470b-9cb5-774c6596afc8",
29           "type": "door"
30         }
31       ],
32       "schedule_id": "58c0f89b-f35c-4d2c-af7b-8b8918df2c31"
33     },
34     {
35       "id": "edbc80df-3698-49fd-8b53-f1867f104947",
36       "name": "TEST",
37       "resources": [
38         {
39           "id": "d5573467-d6b3-4e8f-8e48-8a322b91664a",
40           "type": "door_group"
41         },
```

```

42         {
43             "id": "5c496423-6d25-4e4f-8cdf-95ad5135188a",
44             "type": "door_group"
45         },
46         {
47             "id": "6ff875d2-af87-470b-9cb5-774c6596afc8",
48             "type": "door"
49         }
50     ],
51     "schedule_id": "73facd6c-839e-4521-a4f4-c07e1d44e748"
52 }
53 ],
54 "msg": "success"
55 }

```

5.7 Holiday Group Schemas

A holiday group refers to a collection of holidays.

Parameter	Type	Description
id	String	Identity ID of the holiday group.
name	String	Name of the holiday group.
is_default	Boolean	Indicate whether the holiday group is the system default.
description	String	Description of the holiday group.
holidays	Array[Object]	Show a list of the holidays within the holiday group.
holidays[].description	String	Description of the holiday.
holidays[].id	String	Identity ID of the holiday.
holidays[].name	String	Name of the holiday.
holidays[].repeat	Boolean	Indicate whether the holiday repeats annually.
holidays[].start_time	String	Start time of the holiday, provided in UTC format according to RFC3339.
holidays[].end_time	String	End time of the holiday, provided in UTC format according to RFC3339.

5.8 Create Holiday Group

This API allows you to create a holiday group.

- Request URL: `/api/v1/developer/access_policies/holiday_groups`
- Permission Key: `edit:policy`
- Method: `POST`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Body

Parameter	Required	Type	Description	Example
name	T	String	Name of the holiday group.	
description	F	String	Description of the holiday group.	
holidays	F	Array[Object]	Show a list of the holidays within the holiday group.	
holidays[].description	F	String	Description of the holiday.	
holidays[].name	F	String	Name of the holiday.	
holidays[].repeat	F	Boolean	Indicate whether the holiday repeats annually.	
holidays[].is_template	F	Boolean	Indicate whether the holiday is created using a holiday group template.	
holidays[].start_time	F	String	Start time of the holiday, provided in UTC format according to RFC3339.	2023-08-25T00:00:00Z
holidays[].end_time	F	String	End time of the holiday, provided in UTC format according to RFC3339.	2023-08-26T00:00:00Z

Response Body

Parameter	Required	Type	Description	Related API	Purpose
id	T	String	Identity ID of the holiday group.	<code>/api/v1/developer/access_policies/schedules</code>	Used to add a holiday group to the schedule.

Schemas: [Schemas](#)

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```
1 curl '{{host}}/api/v1/developer/access_policies/holiday_groups'
2   -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3   -H 'accept: application/json'
4   -H 'content-type: application/json' --data-raw
5   '{
6     "name": "Holiday Group-169286791557142",
```

```

7     "holidays": [
8         {
9             "name": "Holiday Name 1",
10            "description": "",
11            "repeat": false,
12            "start_time": "2023-08-25T00:00:00Z",
13            "end_time": "2023-08-26T00:00:00Z"
14        },
15        {
16            "name": "Holiday Name 2",
17            "description": "",
18            "repeat": false,
19            "start_time": "2023-08-26T00:00:00Z",
20            "end_time": "2023-08-27T00:00:00Z"
21        }
22    ]
23 }'

```

Response Sample

```

1  {
2      "code": "SUCCESS",
3      "data": {
4          "description": "",
5          "holidays": [
6              {
7                  "description": "",
8                  "end_time": "2023-08-26 00:00:00Z",
9                  "id": "8900533d-03be-4f84-832d-54ff59905759",
10                 "name": "Holiday Name 1",
11                 "repeat": false,
12                 "start_time": "2023-08-25 00:00:00Z"
13             },
14             {
15                 "name": "holiday-2023-08-26",
16                 "end_time": "2023-08-27 00:00:00Z",
17                 "id": "9fff81cc-d476-40c4-80f9-d510451ce2cd",
18                 "name": "Holiday Name 2",
19                 "repeat": false,
20                 "start_time": "2023-08-26 00:00:00Z"
21             }
22         ],
23         "id": "7be7a7a0-818f-4f76-98c3-1c38957f4dca",
24         "is_default": false,
25         "name": "Holiday Group-169286791557142",
26         "template_name": ""
27     },
28     "msg": "success"

```

5.9 Update Holiday Group

This API allows you to update a holiday group.

- Request URL: `/api/v1/developer/access_policies/holiday_groups/:id`
- Permission Key: `edit:policy`
- Method: `PUT`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description	Example
Id	T	String	Identity ID of the holiday group.	

Request Body

Parameter	Required	Type	Description	Example
name	T	String	Name of the holiday group.	
description	F	String	Description of the holiday group.	
holidays	F	Array[Object]	Show a list of the holidays within the holiday group. Omit this parameter if it doesn't need to be updated.	
holidays[].id	F	String	Identity ID of the holiday. Omit this parameter if it doesn't need to be updated.	Get it from the API <code>/api/v1/developer/access_policies/holiday_groups</code>
holidays[].description	F	String	Description of the holiday.	
holidays[].name	F	String	Name of the holiday.	
holidays[].repeat	F	Boolean	Indicate whether the holiday repeats annually.	
holidays[].start_time	F	String	Start time of the holiday, provided in UTC format according to RFC3339.	2023-08-25T00:00:00Z
holidays[].end_time	F	String	End time of the holiday, provided in UTC format according to RFC3339.	2023-08-26T00:00:00Z

Response Body

Parameter	Required	Type	Description	Related API	Purpose
id	T	String	Identity ID of the holiday group.	/api/v1/developer/access_policies/schedules	Used to add a holiday group to the schedule.

Schemas: [Schemas](#)

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```
1 curl -XPUT '{{host}}/api/v1/developer/access_policies/holiday_groups/7be7a7a0-818f-
2 4f76-98c3-1c38957f4dca'
3 -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
4 -H 'accept: application/json'
5 -H 'content-type: application/json' --data-raw
6 '{
7   "name": "Holiday Group-169286791557142",
8   "holidays": [
9     {
10      "name": "Holiday Name 1",
11      "description": "",
12      "repeat": false,
13      "start_time": "2023-08-25T00:00:00Z",
14      "end_time": "2023-08-26T00:00:00Z"
15    },# add a new holiday
16    {
17      "id":"d23a4226-765f-4967-b84f-6dfd53f33c89", # update an existing
18      holiday
19      "name": "Holiday Name 2",
20      "description": "",
21      "repeat": false,
22      "start_time": "2023-08-26T00:00:00Z",
23      "end_time": "2023-08-27T00:00:00Z"
24    }
25  ]
26 }'
```

Response Sample

```
1 {
2   "code": "SUCCESS",
3   "data": {
4     "description": "",
5     "holidays": [
6       {
7         "description": "",
```

```

8         "end_time": "2023-08-26 00:00:00Z",
9         "id": "8900533d-03be-4f84-832d-54ff59905759",
10        "name": "Holiday Name 1",
11        "repeat": false,
12        "start_time": "2023-08-25 00:00:00Z"
13    },
14    {
15        "description": "",
16        "end_time": "2023-08-27 00:00:00Z",
17        "id": "9fff81cc-d476-40c4-80f9-d510451ce2cd",
18        "name": "Holiday Name 2",
19        "repeat": false,
20        "start_time": "2023-08-26 00:00:00Z"
21    }
22 ],
23 "id": "7be7a7a0-818f-4f76-98c3-1c38957f4dca",
24 "is_default": false,
25 "name": "Holiday Group-169286791557142",
26 "template_name": ""
27 },
28 "msg": "success"
29 }

```

5.10 Delete Holiday Group

This API allows you to delete a holiday group.

- Request URL: `/api/v1/developer/access_policies/holiday_groups/:id`
- Permission Key: `edit:policy`
- Method: `DELETE`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description	Related API
id	T	String	Identity ID of the holiday group.	<code>/api/v1/developer/access_policies/holiday_groups</code>

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```
1 curl -XDELETE '{{host}}/api/v1/developer/access_policies/holiday_groups/7be7a7a0-
2     818f-4f76-98c3-1c38957f4dca'
3     -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
4     -H 'accept: application/json'
5     -H 'content-type: application/json'
```

Response Sample

```
1 {
2     "code": "SUCCESS",
3     "data": "success",
4     "msg": "success"
5 }
```

5.11 Fetch Holiday Group

This API allows you to fetch a holiday group.

- Request URL: `/api/v1/developer/access_policies/holiday_groups/:id`
- Permission Key: `view:policy`
- Method: `GET`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Body

Parameter	Required	Type	Description
Id	T	String	Identity ID of the holiday group.

Response Body

Parameter	Required	Type	Description	Related API	Purpose
id	T	String	Identity ID of the holiday group.	<code>/api/v1/developer/access_policies/schedules</code>	Used to add a holiday group to the schedule.

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```
1 curl -XGET '{{host}}/api/v1/developer/access_policies/holiday_groups/7be7a7a0-818f-4f76-98c3-1c38957f4dca'
2     -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3     -H 'accept: application/json'
4     -H 'content-type: application/json'
```

Response Sample

```
1 {
2     "code": "SUCCESS",
3     "data": {
4         "description": "",
5         "holidays": [
6             {
7                 "description": "",
8                 "end_time": "2023-08-26 00:00:00Z",
9                 "id": "8900533d-03be-4f84-832d-54ff59905759",
10                "name": "Holiday Name 1",
11                "repeat": false,
12                "start_time": "2023-08-25 00:00:00Z"
13            },
14            {
15                "description": "",
16                "end_time": "2023-08-27 00:00:00Z",
17                "id": "9fff81cc-d476-40c4-80f9-d510451ce2cd",
18                "name": "Holiday Name 2",
19                "repeat": false,
20                "start_time": "2023-08-26 00:00:00Z"
21            }
22        ],
23        "id": "7be7a7a0-818f-4f76-98c3-1c38957f4dca",
24        "is_default": false,
25        "name": "Holiday Group-169286791557142",
26        "template_name": ""
27    },
28    "msg": "success"
29 }
```

5.12 Fetch All Holiday Groups

This API allows you to fetch the list of all holiday groups.

- Request URL: `/api/v1/developer/access_policies/holiday_groups`
- Permission Key: `view:policy`
- Method: `GET`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Body

Parameter	Required	Type	Description
Id	T	String	Identity ID of the holiday group.

Response Body

Parameter	Required	Type	Description	Related API	Purpose
id	T	String	Identity ID of the holiday group.	<code>/api/v1/developer/access_policies/schedules</code>	Used to add a holiday group to the schedule.
name	T	String	Name of the holiday group.		
description	T	String	Description of the holiday group.		
count	T	Integer	Total number of holidays.		

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```
1 curl -XGET '{{host}}/api/v1/developer/access_policies/holiday_groups'  
2   -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'  
3   -H 'accept: application/json'  
4   -H 'content-type: application/json'
```

Response Sample

```
1 {  
2   "code": "SUCCESS",  
3   "data": [  
4     {  
5       "count": 0,  
6       "description": "",
```

```
7     "id": "8cc22b49-a7f4-49a6-9f04-044444992d6c",
8     "is_default": true,
9     "name": "No Holidays"
10  },
11  {
12     "count": 2,
13     "description": "",
14     "id": "86c634da-7b2c-411c-a2c1-1495d089c719",
15     "is_default": false,
16     "name": "Holiday Group-1692867312225"
17  }
18 ],
19 "msg": "success"
20 }
```

5.13 Schedule Schemas

These schemas are utilized for creating time periods for daily visits from Sunday through Saturday. The primary purpose of these schemas is to facilitate the assignment of access policies to users.

Parameter	Type	Description
id	String	Identity ID of the schedule.
name	String	Name of the schedule.
is_default	Boolean	Indicate whether the schedule is the system default.
type	String	Contains the <code>access</code> type, which is assigned to a user along with an access policy.
weekly	Object	The customizable scheduling strategy for each day from Sunday to Saturday. If not specified, it means access is allowed every day.
weekly.monday	Array[Object]	Specify the daily access time period from Sunday to Saturday.
weekly.monday[].start_time	String	Start time of the access time period.
weekly.monday[].end_time	String	End time of the access time period.
holiday_group_id	String	Identity ID of the holiday group.
holiday_group.id	String	Identity ID of the holiday group.
holiday_group.name	String	Name of the holiday group.
holiday_group.is_default	Boolean	Indicate whether the holiday group is the system default.
holiday_group.description	String	Description of the holiday group.
holiday_group.holidays	Array[Object]	Show a list of the holidays within the holiday group.
holiday_group.holidays[].description	String	Description of the holiday.
holiday_group.holidays[].id	String	Identity ID of the holiday.
holiday_group.holidays[].name	String	Name of the holiday.
holiday_group.holidays[].repeat	Boolean	Indicate whether the holiday repeats annually.
holiday_group.holidays[].start_time	String	Start time of the holiday, provided in UTC format according to RFC3339.
holiday_group.holidays[].end_time	String	End time of the holiday, provided in UTC format according to RFC3339.

5.14 Create Schedule

This API allows you to create a door access schedule.

- Request URL: `/api/v1/developer/access_policies/schedules`
- Permission Key: `edit:policy`
- Method: `POST`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Body

Parameter	Required	Type	Description	Example
name	T	String	The name of the schedule. This needs to be globally unique.	schedule-1789067565323
week_schedule	T	Object	The customizable scheduling strategy for each day from Sunday to Saturday. If not specified, it means access is allowed every day.	
week_schedule.monday	T	Array[Object]	Specify the daily access time period from Sunday to Saturday.	
week_schedule.monday[0].start_time	T	String	Start time of the access time period.	00:00:00
week_schedule.monday[0].end_time	T	String	End time of the access time period.	23:59:59
holiday_group_id	F	String	Identity ID of the holiday group. The default is <code>no_holidays</code> system group.	75660081-431b-4dbe-9b98-e0257877118e

Response Body

Parameter	Required	Type	Description	Related API	Purpose
id	T	String	Identity ID of the schedule.	<code>/api/v1/developer/access_policies</code>	Used to add a schedule to the access policy.

Schemas: [Schemas](#)

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```
1 curl '{{host}}/api/v1/developer/access_policies/schedules'  
2   -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'  
3   -H 'accept: application/json'  
4   -H 'content-type: application/json' --data-raw  
5   '{  
6     "name": "schedule-1688977094169",  
7     "week_schedule": {  
8       "sunday": [],  
9       "monday": [  
10        {  
11          "start_time": "10:00:00",  
12          "end_time": "17:00:59"  
13        }  
14      ],  
15      "tuesday": [  
16        {  
17          "start_time": "10:00:00",  
18          "end_time": "17:00:59"  
19        }  
20      ]  
21    }  
22  }'
```

```

16     {
17         "start_time": "10:00:00",
18         "end_time": "17:00:59"
19     }
20 ],
21 "wednesday": [
22     {
23         "start_time": "10:00:00",
24         "end_time": "17:00:59"
25     }
26 ],
27 "thursday": [],
28 "friday": [
29     {
30         "start_time": "10:00:00",
31         "end_time": "17:00:59"
32     }
33 ],
34 "saturday": []
35 },
36 "holiday_group_id": "75660081-431b-4dbe-9b98-e0257877118e"
37 }'

```

Response Sample

```

1  {
2    "code": "SUCCESS",
3    "data": {
4      "id": "1d31b648-b8ff-4bd1-b742-60dbd70592cd",
5      "is_default": false,
6      "name": "schedule-1688977094169",
7      "type": "access",
8      "weekly": {
9        "friday": [
10         {
11           "end_time": "17:00:59",
12           "start_time": "10:00:00"
13         }
14       ],
15       "monday": [
16         {
17           "end_time": "17:00:59",
18           "start_time": "10:00:00"
19         }
20       ],
21       "saturday": [],
22       "sunday": [],
23       "thursday": [],

```

```

24     "tuesday": [
25         {
26             "end_time": "17:00:59",
27             "start_time": "10:00:00"
28         }
29     ],
30     "wednesday": [
31         {
32             "end_time": "17:00:59",
33             "start_time": "10:00:00"
34         }
35     ]
36 },
37 "holiday_group_id": "75660081-431b-4dbe-9b98-e0257877118e",
38 "holiday_group": {
39     "description": "",
40     "holidays": [
41         {
42             "description": "",
43             "end_time": "2023-08-26 00:00:00Z",
44             "id": "d51777c4-9559-45aa-8e23-434995d9d2a1",
45             "is_template": false,
46             "name": "Holiday Name 1",
47             "repeat": false,
48             "start_time": "2023-08-25 00:00:00Z"
49         },
50         {
51             "description": "",
52             "end_time": "2023-08-27 00:00:00Z",
53             "id": "d23a4226-765f-4967-b84f-6dfd53f33c89",
54             "is_template": false,
55             "name": "Holiday Name 2",
56             "repeat": false,
57             "start_time": "2023-08-26 00:00:00Z"
58         }
59     ],
60     "id": "75660081-431b-4dbe-9b98-e0257877118e",
61     "is_default": false,
62     "name": "Holiday Group-1692867915571423",
63     "template_name": ""
64 }
65 },
66 "msg": "success"
67 }

```

5.15 Update Schedule

This API allows you to update a door access schedule.

- Request URL: `/api/v1/developer/access_policies/schedules/:id`
- Permission Key: `edit:policy`
- Method: `PUT`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description	Example
Id	T	String	Identity ID of the schedule.	

Request Body

Parameter	Required	Type	Description	Example
name	F	String	The name of the schedule. This needs to be globally unique. Omit this parameter if it doesn't need to be updated.	schedule-1789067565323
week_schedule	F	Object	The customizable scheduling strategy for each day from Sunday to Saturday. If not specified, it means access is allowed every day. Omit this parameter if it doesn't need to be updated.	
week_schedule.monday	F	Array[Object]	Specify the daily access time period from Sunday to Saturday.	
week_schedule.monday[0].start_time	F	String	Start time of the access time period.	00:00:00
week_schedule.monday[0].end_time	F	String	End time of the access time period.	23:59:59
holiday_group_id	F	String	Identity ID of the holiday group. The default is <code>no_holidays</code> system group.	75660081-431b-4dbe-9b98-e0257877118e

Response Body

Parameter	Required	Type	Description	Related API	Purpose
id	T	String	Identity ID of the schedule.	<code>/api/v1/developer/access_policies</code>	Used to add a schedule to the access policy.

Schemas: [Schemas](#)

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```
1 curl -XPUT '{{host}}/api/v1/developer/access_policies/schedules/1d31b648-b8ff-4bd1-
2     -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3     -H 'accept: application/json'
4     -H 'content-type: application/json' --data-raw
5     '{
6         "name": "schedule-1688977094169",
7         "holiday_group_id": "75660081-431b-4dbe-9b98-e0257877118e",
8         "week_schedule": {
9             "sunday": [],
10            "monday": [
11                {
12                    "start_time": "10:00:00",
13                    "end_time": "17:00:59"
14                }
15            ],
16            "tuesday": [
17                {
18                    "start_time": "10:00:00",
19                    "end_time": "17:00:59"
20                }
21            ],
22            "wednesday": [
23                {
24                    "start_time": "10:00:00",
25                    "end_time": "17:00:59"
26                }
27            ],
28            "thursday": [
29                {
30                    "start_time": "10:00:00",
31                    "end_time": "17:01:59"
32                }
33            ],
34            "friday": [
35                {
36                    "start_time": "10:00:00",
37                    "end_time": "17:00:59"
38                }
39            ],
40            "saturday": []
41        }
42    }'
```

Response Sample

```
1 {
2   "code": "SUCCESS",
3   "data": {},
4   "msg": "success"
5 }
```

5.16 Fetch Schedule

This API allows you to fetch a door access schedule.

- Request URL: `/api/v1/developer/access_policies/schedules/:id`
- Permission Key: `view:policy`
- Method: `GET`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description	Example
Id	T	String	Identity ID of the schedule.	

Response Body

Parameter	Required	Type	Description	Example
name	T	String	Name of the schedule.	
week_schedule	T	Object	The customizable scheduling strategy for each day from Sunday to Saturday. If not specified, it means access is allowed every day.	
holiday_group	T	Object	Show the assigned holiday group.	

Schemas: [Schemas](#)

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```
1  curl --location '{host}}/api/v1/developer/access_policies/schedules/908079e7-e26b-
2  4951-9073-d775446d3584' --header 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
```

Response Sample

```
1  {
2  "code": "SUCCESS",
3  "data": {
4      "id": "1d31b648-b8ff-4bd1-b742-60dbd70592cd",
5      "is_default": false,
6      "name": "schedule-1688977094169",
7      "type": "access",
8      "weekly": {
9          "friday": [
10             {
11                 "end_time": "17:00:59",
12                 "start_time": "10:00:00"
13             }
14         ],
15         "monday": [
16             {
17                 "end_time": "17:00:59",
18                 "start_time": "10:00:00"
19             }
20         ],
21         "saturday": [],
22         "sunday": [],
23         "thursday": [
24             {
25                 "end_time": "17:01:59",
26                 "start_time": "10:00:00"
27             }
28         ],
29         "tuesday": [
30             {
31                 "end_time": "17:00:59",
32                 "start_time": "10:00:00"
33             }
34         ],
35         "wednesday": [
36             {
37                 "end_time": "17:00:59",
38                 "start_time": "10:00:00"
39             }
40         ]
41     }
42 }
```

```

39     }
40   ]
41 },
42 "holiday_group_id": "75660081-431b-4dbe-9b98-e0257877118e",
43 "holiday_group": {
44   "description": "",
45   "holidays": [
46     {
47       "description": "",
48       "end_time": "2023-08-26 00:00:00Z",
49       "id": "d51777c4-9559-45aa-8e23-434995d9d2a1",
50       "is_template": false,
51       "name": "Holiday Name 1",
52       "repeat": false,
53       "start_time": "2023-08-25 00:00:00Z"
54     },
55     {
56       "description": "",
57       "end_time": "2023-08-27 00:00:00Z",
58       "id": "d23a4226-765f-4967-b84f-6dfd53f33c89",
59       "is_template": false,
60       "name": "Holiday Name 2",
61       "repeat": false,
62       "start_time": "2023-08-26 00:00:00Z"
63     }
64   ],
65   "id": "75660081-431b-4dbe-9b98-e0257877118e",
66   "is_default": false,
67   "name": "Holiday Group-16928679155714",
68   "template_name": ""
69 },
70 },
71 "msg": "success"
72 }

```

5.17 Fetch All Schedules

This API allows you to fetch all door access schedules.

- Request URL: `/api/v1/developer/access_policies/schedules`
- Permission Key: `view:policy`
- Method: `GET`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Response Body

Parameter	Required	Type	Description	Example
Data	T	Array[Object]		

Schemas: [Schemas](#)

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```
1 curl --location '{{host}}/api/v1/developer/access_policies/schedules'  
2 -H 'Authorization: Bearer WHFmHRuX4I7sB2oDkD6wHg'  
3
```

Response Sample

```
1  {  
2    "code": "SUCCESS",  
3    "data": [  
4      {  
5        "id": "73facd6c-839e-4521-a4f4-c07e1d44e748",  
6        "holiday_group_id": "75660081-431b-4dbe-9b98-e0257877118e",  
7        "is_default": true,  
8        "name": "Always Access",  
9        "status": 1,  
10       "type": "access"  
11     },  
12     {  
13       "id": "58c0f89b-f35c-4d2c-af7b-8b8918df2c31",  
14       "holiday_group_id": "75660081-431b-4dbe-9b98-e0257877118e",  
15       "is_default": false,  
16       "name": "UNVR Schedule",  
17       "status": 1,  
18       "type": "access"  
19     }  
20   ],  
21   "msg": "success"  
22 }
```

5.18 Delete Schedule

This API allows you to delete a door access schedule.

- Request URL: `/api/v1/developer/access_policies/schedules/:id`
- Permission Key: `edit:policy`
- Method: `DELETE`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description	Example
Id	T	String	Identity ID of the schedule.	

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```
1 curl -XDELETE '{{host}}/api/v1/developer/access_policies/schedules/f5355214-3a45-4e0b-9245-12df7075df37'
2 -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3 -H 'accept: application/json'
4 -H 'content-type: application/json'
```

Response Sample

```
1 { "code": "SUCCESS", "msg": "success", "data": "success" }
```

6. Credential

The APIs here are designed for managing PIN codes, NFC cards, and other related credentials.

6.1 Generate PIN Code

This API enables you to generate a PIN code. A PIN code can be assigned to a visitor or user, and once assigned, they can use it to unlock doors.

- Request URL: `/api/v1/developer/credentials/pin_codes`
- Permission Key: `view:credential`
- Method: `POST`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Response Body

Parameter	Required	Type	Description	Related API	Purpose
data	T	String	PIN code	<code>/api/v1/developer/users;</code> <code>/api/v1/developer/visitors</code>	Assign the PIN code to the created user or visitor.

Request Sample: Shell/cURL

The request body should be a JSON object containing the following fields:

```
1 curl --location --request POST
   'https://{{host}}/api/v1/developer/credentials/pin_codes'
2   -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3   -H 'Content-Type: application/json' \
4   --data ''
```

Response Sample

```
1 {
2   "code": "SUCCESS",
3   "data": "67203419",
4   "msg": "success"
5 }
```

6.2 Enroll NFC Card

Wake up a UA reader and create a session to enroll an NFC card.

- Request URL: `/api/v1/developer/credentials/nfc_cards/sessions`
- Permission Key: `edit:credential`
- Method: `POST`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Body

Parameter	Required	Type	Description	How to Get It?
device_id	T	String	Identity ID of the device.	Get it from the API <code>/api/v1/developer/devices</code> .
reset_ua_card	F	Boolean		This option allows you to reset an NFC card already enrolled at another site.

Response Body

Parameter	Required	Type	Description	Related API	Purpose
session_id	T	String	The session for enrolling an NFC card.	<code>/api/v1/developer/credentials/nfc_cards/sessions/{session_id}</code>	NFC card polling result.

Request Sample

```
1 curl '{{host}}/api/v1/developer/credentials/nfc_cards/sessions'  
2   -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'  
3   -H 'accept: application/json'  
4   -H 'content-type: application/json'  
5   --data-raw '{"device_id": "0418d6a2bb7a}"'
```

Response Sample

```
1 {  
2   "code": "SUCCESS",  
3   "msg": "success",  
4   "data": {  
5     "session_id": "9416409b-3608-4cad-8bb3-7227108ffe9b"  
6   }  
7 }
```


6.3 Fetch NFC Card Enrollment Status

This API enables you to poll a UA reader to fetch the NFC card enrollment status and the generated card tokens.

- Request URL: `/api/v1/developer/credentials/nfc_cards/sessions/:id`
- Permission Key: `edit:credential`
- Method: `GET`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Body

Parameter	Required	Type	Description	Related API	How to Get It?
id	T	String	The session for enrolling an NFC card.	<code>/api/v1/developer/users;</code> <code>/api/v1/developer/visitors</code>	Get it from the API <code>/api/v1/developer/credentials/nfc_cards/sessions.</code>

Response Body

Parameter	Required	Type	Description	Related API	Purpose
token	T	String	Unique NFC card token.	<code>/api/v1/developer/users;</code> <code>/api/v1/developer/visitors</code>	The generated card token is used to bind to a user or visitor.
card_id	T	String	Display ID of the NFC card.		

Request Sample

```
1 GET /api/v1/developer/credentials/nfc_cards/sessions/e8a97c52-6676-4c48-8589-bd518afc4094
```

Response Sample

```

1  {
2      "code": "SUCCESS",
3      "msg": "success",
4      "data": {
5          "card_id": "014A3151",
6          "token": "821f90b262e90c5c0fbcddf3d6d2f3b94cc015d6e8104ab4fb96e4c8b8e90cb7"
7      }
8  }

```

6.4 Remove a Session Created for NFC Card Enrollment

This API enables you to remove a session created for enrolling an NFC card.

- Request URL: `/api/v1/developer/credentials/nfc_cards/sessions/:id`
- Permission Key: `edit:credential`
- Method: `DELETE`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Body

Parameter	Required	Type	Description	Related API	How to Get It?
id	T	String	The session for enrolling an NFC card.	<code>/api/v1/developer/users;</code> <code>/api/v1/developer/visitors</code>	Get it from the API <code>/api/v1/credentials/nfc_cards/sessions.</code>

Request Sample

```

1  DELETE /api/v1/developer/credentials/nfc_cards/sessions/e8a97c52-6676-4c48-8589-
      bd518afc4094

```

Response Sample

```

1  { "code": "SUCCESS", "msg": "success", "data": "success" }

```

7. Space

The APIs here are designed for managing spaces, including doors, door groups, and floors.

7.1 Fetch Door Group Topology

Fetch all current floor and door resources for access policy and visitor assignment purposes.

- Request URL: `/api/v1/developer/door_groups/topology`
- Permission Key: `view:space`
- Method: `GET`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Response Body

Parameter`	Required	Type	Description	Purpose	Related API
id	F	String	Identity ID of the door group.	Used when creating an access policy.	
type	T	String	<code>enum group_type {building,access}</code> The <code>building</code> type contains all the doors; the <code>access</code> type represents all the customized door groups.		<code>access:</code> <code>/api/v1/developer/door_groups</code>
resource_topologies	T	Array[Object]	Contain information about the floor and all its associated doors.	Bind policies or specify available locations for visitors to access.	<code>/api/v1/developer/access_policies</code> <code>/api/v1/developer/visitors</code>
resource_topologies[].id	T	String	Identity ID of the floor.		
resource_topologies[].type	T	String	Type of the floor.		
resource_topologies[].name	T	String	Name of the floor.		
resource_topologies[].resources	T	Array[Object]	Contain all the doors on the floor.		
resource_topologies[].resources.id	T	String	Identity ID of the door.		
resource_topologies[].resources.name	T	String	Name of the door.		
resource_topologies[].resources.type	T	String	Type of the door.		

Request Sample

The request body should be a JSON object containing the following fields:

```
1 curl -X GET '{{host}}/api/v1/developer/door_groups/topology'
2   -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3   -H 'accept: application/json'
4   -H 'content-type: application/json'
```

Response Sample

```
1 {
2   "code": "SUCCESS",
3   "data": [
4     {
5       "id": "d5573467-d6b3-4e8f-8e48-8a322b91664a",
6       "name": "All Doors",
7       "resource_topologies": [
8         {
9           "id": "9bee6e0e-108d-4c52-9107-76f2c7dea4f1",
10          "name": "Main Floor",
11          "resources": [
12            {
13              "id": "6ff875d2-af87-470b-9cb5-774c6596afc8",
14              "name": "Door 3855",
15              "type": "door"
16            }
17          ],
18          "type": "floor"
19        }
20      ],
21      "type": "building"
22    },
23    {
24      "id": "5c496423-6d25-4e4f-8cdf-95ad5135188a",
25      "name": "customized group",
26      "resource_topologies": [
27        {
28          "id": "9bee6e0e-108d-4c52-9107-76f2c7dea4f1",
29          "name": "Main Floor",
30          "resources": [
31            {
32              "id": "6ff875d2-af87-470b-9cb5-774c6596afc8",
33              "name": "Door 3855",
34              "type": "door"
35            }
36          ],
37          "type": "floor"
38        }
39      ],
40      "type": "building"
41    }
42  ]
43 }
```

```

38         }
39     ],
40     "type": "access"
41 }
42 ],
43 "msg": "success"
44 }

```

7.2 Create Door Group

This API allows you to create a door group.

- Request URL: `/api/v1/developer/door_groups`
- Permission Key: `edit:space`
- Method: `POST`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Body

Parameter	Required	Type	Description	Example	How to Get It?
group_name	T	String	Name of the door group. This needs to be globally unique.		
resources	T	Array[String]	Collection of door ID.		<code>/api/v1/developer/door_groups/topology</code>

Response Body

Parameter	Required	Type	Description	Purpose	Related API
id	T	String	Identity ID of the door group.	Used to assign access group to visitor and access policy.	<code>/api/v1/developer/visitors;</code> <code>/api/v1/developer/access_policies;</code>
name	T	String	Name of the door group.		
resources	T	String	All doors contained under the group.		
resources[].id	T	String	Identity ID of the door.		
resources[].type	T	String	Type of the door.		

Request Sample

The request body should be a JSON object containing the following fields:

```
1 curl '{{host}}/api/v1/developer/door_groups'  
2     -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'  
3     -H 'accept: application/json'  
4     -H 'content-type: application/json'  
5     --data-raw '{  
6         "group_name": "Test",  
7         "resources": [  
8             "6ff875d2-af87-470b-9cb5-774c6596afc8"  
9         ]  
10    }'
```

Response Sample

```
1 {  
2     "code": "SUCCESS",  
3     "data": {  
4         "id": "0140fa3d-8973-4305-a0ce-5306ae277878",  
5         "name": "Customized Door Group",  
6         "resources": [  
7             {  
8                 "id": "6ff875d2-af87-470b-9cb5-774c6596afc8",  
9                 "type": "door"  
10            }  
11        ],  
12        "type": "access"  
13    },  
14    "msg": "success"  
15 }
```

7.3 Fetch Door Group

This API allows you to fetch door group details.

- Request URL: `/api/v1/developer/door_groups/:id`
- Permission Key: `view:space`
- Method: `GET`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description
Id	T	String	Identity ID of the door group.

Response Body

Parameter	Required	Type	Description	Purpose	Related API
id	T	String	Identity ID of the door group.	Used to assign access group to visitor and access policy.	<code>/api/v1/developer/visitors;</code> <code>/api/v1/developer/access_policies;</code>
name	T	String	Name of the door group.		
type	t	String	Include door access and building resources. <code>enum type {access,building}</code> The <code>building</code> type stands for all doors, which is a special group obtained from the topology API . The <code>access</code> type represents all custom door groups.		
resources	T	String	All doors contained under the group.		
resources[].id	T	String	Identity ID of the door.		
resources[].type	T	String	The access type represents all custom door group types.		

Request Sample

The request body should be a JSON object containing the following fields:

```
1 curl '{{host}}/api/v1/developer/door_groups/d5573467-d6b3-4e8f-8e48-8a322b91664a'  
2   -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'  
3   -H 'accept: application/json'  
4   -H 'content-type: application/json'  
5
```

Response Sample

```
1 # Group type is building
2 {
3   "code": "SUCCESS",
4   "data": {
5     "id": "d5573467-d6b3-4e8f-8e48-8a322b91664a",
6     "name": "All Doors",
7     "resources": [
8       {
9         "id": "6ff875d2-af87-470b-9cb5-774c6596afc8",
10        "name": "Door 3855",
11        "type": "door"
12      },
13      {
14        "id": "7cc1823f-9cdb-447b-b01b-4cb2abc661c0",
15        "name": "A2 Door",
16        "type": "door"
17      },
18      {
19        "id": "ececa68e-239f-4b82-adc4-0c9ce70c60ff",
20        "name": "A3",
21        "type": "door"
22      }
23    ],
24    "type": "building"
25  },
26  "msg": "success"
27 }
28
29 # Customized groups
30 {
31   "code": "SUCCESS",
32   "data": {
33     "id": "1be0c995-0347-4cb2-93b3-66a9624af568",
34     "name": "321321321",
35     "resource_topologies": [
36       {
37         "id": "9bee6e0e-108d-4c52-9107-76f2c7dea4f1",
38         "name": "Main Floor",
39         "resources": [
40           {
41             "id": "6ff875d2-af87-470b-9cb5-774c6596afc8",
42             "name": "Door 3855",
43             "type": "door"
44           }, {
45             "id": "7cc1823f-9cdb-447b-b01b-4cb2abc661c0",
46             "name": "A2 Door",
47             "type": "door"
48           }
49         ]
50       }
51     ]
52   }
53 }
```



```

48         }, {
49             "id": "ececa68e-239f-4b82-adc4-0c9ce70c60ff",
50             "name": "A3",
51             "type": "door"
52         }
53     ],
54     "type": "floor"
55 }
56 ],
57 "resources": [
58     {
59         "id": "6ff875d2-af87-470b-9cb5-774c6596afc8",
60         "type": "door"
61     }
62 ],
63 "type": "access"
64 },
65 "msg": "success"
66 }

```

7.4 Update Door Group

This API allows you to update door group details.

- Request URL: `/api/v1/developer/door_groups/:id`
- Permission Key: `edit:space`
- Method: `PUT`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description
id	T	String	Identity ID of the door group.

Request Body

Parameter	Required	Type	Description	Example	How to Get It?
group_name	F	String	Name of door group. Omit this parameter if it doesn't need to be updated.		
resources	F	Array[String]	Collection of door identifier ID. Omit this parameter if it doesn't need to be updated.		<code>/api/v1/developer/door_groups/topology</code>

Response Body

Parameter	Required	Type	Description	Purpose	Related API
id	T	String	Identity ID of the door group.	Used to assign access group to visitor and access policy.	<code>/api/v1/developer/visitors;</code> <code>/api/v1/developer/access_policies;</code>
name	T	String	Name of the door group.		
resources	T	String	All doors contained under the group.		
resources[].id	T	String	Identity ID of the door.		
resources[].type	T	String	Type of the door.		

Request Sample

The request body should be a JSON object containing the following fields:

```
1  curl -X PUT '{{host}}/api/v1/developer/door_groups/0140fa3d-8973-4305-a0ce-
2      5306ae277878'
3      -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
4      -H 'accept: application/json'
5      -H 'content-type: application/json'
6      --data-raw '{
7          "resources": [
8              "6ff875d2-af87-470b-9cb5-774c6596afc8",
9              "5a2c3d4e-1f6b-4c8d-9e0f-2a3b4c5d6e7f",
10             "2p3q4r5s-6t7u-8v9w-x0y1-z2a3b4c5d6e"
11         ]
12     }'
```

Delete all door resources

```
13  curl -X PUT '{{host}}/api/v1/developer/door_groups/0140fa3d-8973-4305-a0ce-
14      5306ae277878'
15      -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
16      -H 'accept: application/json'
17      -H 'content-type: application/json'
18      --data-raw '{
19          "resources": []
20     }'
```

Response Sample

```
1 {
2   "code": "SUCCESS",
3   "data": {
4     "id": "0140fa3d-8973-4305-a0ce-5306ae277878",
5     "name": "test",
6     "resources": [
7       {
8         "id": "6ff875d2-af87-470b-9cb5-774c6596afc8",
9         "type": "door"
10      }
11    ],
12    "type": "access"
13  },
14  "msg": "success"
15 }
```

7.5 Fetch All Door Groups

This API allows you to fetch the list of all door groups.

- Request URL: `/api/v1/developer/door_groups`
- Permission Key: `view:space`
- Method: `GET`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Response Body

Parameter	Required	Type	Description	Purpose	Related API
id	T	String	Identity ID of the door group.	Used to create a door groups and to open doors remotely, if a device is bound.	<code>/api/v1/developer/door_groups;</code> <code>/api/v1/developer/doors/:id/remote_unlock;</code>
name	T	String	Name of the door group.		
type	t	String	Include door access and building resources. <code>enum type {access,building}</code> The <code>building</code> type represents all doors, which is a special group obtained from the topology API . But the list does not contain the group type <code>building</code> . The <code>access</code> type represents all custom door groups.		
resources	T	String	All doors contained under the group.		
resources[].id	T	String	Identity ID of the door.		
resources[].type	T	String	Type of the door.		

Response Sample

The request body should be a JSON object containing the following fields:

```

1 curl '{{host}}/api/v1/developer/door_groups'
2   -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3   -H 'accept: application/json'
4   -H 'content-type: application/json'
5

```

Response Sample

```

1  {
2    "code": "SUCCESS",
3    "data": [
4      {
5        "id": "5c496423-6d25-4e4f-8cdf-95ad5135188a",
6        "name": "Test",
7        "resources": [
8          {
9            "id": "6ff875d2-af87-470b-9cb5-774c6596afc8",
10           "type": "door"
11         }
12       ],
13       "type": "access"
14     },
15     {
16       "id": "1907cc46-0a73-4077-94c1-95b625bdb0f8",

```

```

17     "name": "Test2",
18     "resources": [
19         {
20             "id": "6ff875d2-af87-470b-9cb5-774c6596afc8",
21             "type": "door"
22         }
23     ],
24     "type": "access"
25 }
26 ],
27 "msg": "success"
28 }

```

7.6 Delete Door Group

This API allows you to delete a door group.

- Request URL: `/api/v1/developer/door_groups/:id`
- Permission Key: `edit:space`
- Method: `DELETE`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description
id	T	String	Identity ID of the door group.

Request Sample

The request body should be a JSON object containing the following fields:

```

1 curl -X DELETE '{host}/api/v1/developer/door_groups/0140fa3d-8973-4305-a0ce-
2     5306ae277878'
3     -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
4     -H 'accept: application/json'
5     -H 'content-type: application/json'

```

Response Sample

```
1 {
2   "code": "SUCCESS",
3   "data": "success",
4   "msg": "success"
5 }
```

7.7 Fetch Door

This API allows you to fetch door details.

- Request URL: `/api/v1/developer/doors/:id`
- Permission Key: `view:space`
- Method: `GET`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description
id	T	String	Identity ID of the door.

Response Body

Parameter	Required	Type	Description	Purpose	Related API
id	T	String	Identity ID of the door group.	1. Used to create a door group. 2. Used to unlock a door remotely, if the door is bound to a hub device.	<code>/api/v1/developer/door_groups;</code> <code>/api/v1/developer/doors/:id/remote_unlock;</code>
name	T	String	Name of the door.		
full_name	T	String	Full name of the door.		
floor_id	T	String	Identity ID of the floor.		
type	T	String	Type of the door.		
door_lock_relay_status	T	String	Door lock status. enum <code>door_lock_relay_status</code> {lock,unlock}		
door_position_status	T	String	DPS: Door position status, including both <code>open</code> and <code>close</code> . A null value means that no device is connected.		

Request Sample

The request body should be a JSON object containing the following fields:

```

1 curl -X GET '{{host}}/api/v1/developer/doors/0ed545f8-2fcd-4839-9021-b39e707f6aa9'
2     -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3     -H 'accept: application/json'
4     -H 'content-type: application/json'

```

Response Sample

```

1 {
2   "code": "SUCCESS",
3   "data": {
4     "door_lock_relay_status": "lock",
5     "door_position_status": "",
6     "floor_id": "3275af8d-3fa7-4902-a11b-011e41c8464a",
7     "full_name": "UNVR - 1F - Main Door",
8     "id": "0ed545f8-2fcd-4839-9021-b39e707f6aa9",
9     "name": "Main Door",
10    "type": "door"
11  },
12  "msg": "success"
13 }

```

7.8 Fetch All Doors

This API allows you to fetch the list of all doors.

- Request URL: `/api/v1/developer/doors`
- Permission Key: `view:space`
- Method: `GET`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Response Body

Parameter	Required	Type	Description	Purpose	Related API
id	T	String	Identity ID of the door group.	1. Used to create a door group. 2. Used to unlock a door remotely, if the door is bound to a hub device.	<code>/api/v1/developer/door_groups;</code> <code>/api/v1/developer/doors/:id/remote_unlock;</code>
name	T	String	Name of the door.		
full_name	T	String	Full name of the door.		
floor_id	T	String	Identity ID of the floor.		
type	T	String	Type of the door.		
is_bind_hub	T	String	Indicate whether the door has bound to a hub device.		
door_lock_relay_status	T	String	Door lock status. <code>enum door_lock_relay_status {lock,unlock}</code>		
door_position_status	T	String	DPS: Door position status, including both <code>open</code> and <code>close</code> . A null value means that no device is connected.		

Request Sample

The request body should be a JSON object containing the following fields:

```

1 curl -X GET '{{host}}/api/v1/developer/doors'
2   -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3   -H 'accept: application/json'
4   -H 'content-type: application/json'

```


Response Sample

```
1  {
2    "code": "SUCCESS",
3    "data": [
4      {
5        "door_lock_relay_status": "unlock",
6        "door_position_status": "open",
7        "floor_id": "23c5db06-b59b-494d-94f1-23e88fbe4909",
8        "full_name": "UNVR - 2F - A2 Door",
9        "id": "0ed545f8-2fcd-4839-9021-b39e707f6aa9",
10       "is_bind_hub": true,
11       "name": "A2 Door",
12       "type": "door"
13     },
14     {
15       "door_lock_relay_status": "lock",
16       "door_position_status": "close",
17       "floor_id": "7c62b4b3-692f-44ea-8eb8-e212833b4e0f",
18       "full_name": "UNVR - 1F - Door 3855",
19       "id": "5785e97b-6123-4596-ba49-b6e51164db9b",
20       "is_bind_hub": true,
21       "name": "Door 3855",
22       "type": "door"
23     }
24   ],
25   "msg": "success"
26 }
```

7.9 Remote Door Unlocking

This API allows you to remotely unlock a door.

- Request URL: `/api/v1/developer/doors/:id/unlock`
- Permission Key: `edit:space`
- Method: `PUT`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Request Path

Parameter	Required	Type	Description
id	T	String	Identity ID of the door.

Request Sample

The request body should be a JSON object containing the following fields:

```
1 curl -X PUT '{{host}}/api/v1/developer/doors/5785e97b-6123-4596-ba49-
2 b6e51164db9b/unlock'
3 -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
4 -H 'accept: application/json'
5 -H 'content-type: application/json'
```

Response Sample

```
1 {
2   "code": "SUCCESS",
3   "data": "success",
4   "msg": "success"
5 }
```

8. Device

The APIs here are designed for device management, including obtaining device lists, device information, device statuses, device configurations, and more.

8.1 Fetch Devices

Obtain a list of all current devices. The device ID is required for enrolling an NFC card.

- Request URL: `/api/v1/developer/devices`
- Permission Key: `view:device`
- Method: `GET`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Response Body

Parameter	Required	Type	Description	Purpose	Related API
id	T	String	Identity ID of the device.	Used for enrolling an NFC card.	<code>/api/v1/developer/credentials/nfc_cards/sessions</code>
name	T	String	Name of the device.		
type	T	String	Type of the device.		
full_name	T	String	Full name of the device.		

Request Sample: Shell/cURL

```
1 curl '{{host}}/api/v1/developer/devices'  
2   -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'  
3   -H 'accept: application/json'
```

Response Body

```
1  {  
2    "code": "SUCCESS",  
3    "data": [  
4      [  
5        {  
6          "full_name": "UNVR - Main Floor - Door 3855 - UA-HUB-3855",  
7          "id": "7483c2773855",
```

```
8         "name": "UA-HUB-3855",
9         "type": "UAH"
10    },
11    {
12        "full_name": "UNVR - Main Floor - Door 3855 - out - UA-LITE-8CED",
13        "id": "f492bfd28ced",
14        "name": "UA-LITE-8CED",
15        "type": "UDA-LITE"
16    },
17    {
18        "full_name": "UNVR - Main Floor - Door 3855 - in - UA-G2-PRO-BB7A",
19        "id": "0418d6a2bb7a",
20        "name": "UA-G2-PRO-BB7A",
21        "type": "UA-G2-PRO"
22    }
23    ]
24 ],
25 "msg": "success"
26 }
```

9. System Log

The APIs here are designed for system log management.

9.1 Topic Reference

Parameter	Description
all	Fetch all logs.
door_openings	Fetch door opening logs.
critical	Fetch logs for device restart, deletion, offline status, and detection.
updates	Fetch device update logs.
device_events	Fetch logs for device online status, device updates, access policy synchronization, and active and inactive door unlock schedules.
admin_activity	Fetch logs for admin activity, such as access policy updates, settings changes, and user management.
visitor	Fetch logs of of visitor-related operations.

9.2 Fetch System Logs

This API enables you to fetch system logs.

- Request URL: `/api/v1/developer/system/logs`
- Permission Key: `view:system_log`
- Method: `POST`

Request Header

Parameter	Required	Type	Description
Authorization	T	String	Token required for authentication and access control.

Query Parameters

Parameter	Required	Type	Description	Example
page_num	F	String	Current page number in the pagination.	1
page_size	F	String	Number of logs per page.	25

Request Body

Parameter	Required	Type	Description	Example
topic	T	String	Fetch different system logs by <code>topic</code> .enum <code>topic</code> {critical,door_openings,updates,device_events,admin_activity,visitor}	door_openings
since	F	Integer	Start time for log fetching.	1689304925
until	F	Integer	End time for log fetching.	1689804925
actor_id	F	String	Identity ID of the actor (user, visitor, and device).	3e1f196e-c97b-4748-aecb-eab5e9c251b2

Response Body

Parameter	Required	Type	Description	Purpose
actor	T	Object	Information about the event operator.	
event	T	Object	Basic information about the event.	
authentication	F	Object	Certification information.	
target	F	Array[Object]	Additional information associated with the event, such as updated information.	

Request Sample: Shell/cURL

```
1 curl '{{host}}/api/v1/developer/system/logs?
   page_size=1&page_num=25&since=0&until=1689304925'
2   -H 'Authorization: Bearer wHFmHRuX4I7sB2oDkD6wHg'
3   -H 'accept: application/json'
4   -H 'content-type: application/json'
5   --data '{
6     "topic": "door_openings",
7     "since": 1690770546,
8     "until": 1690771546,
9     "actor_id": "3e1f196e-c97b-4748-aecb-eab5e9c251b2"
10  }'
```

Response Body

```
1 {
2   "code": "SUCCESS",
3   "data": {
4     "hits": [
5       {
6         "@timestamp": "2023-07-11T12:11:27Z",
7         "_id": "",
8         "_source": {
9           "actor": {
```

```
10         "alternate_id": "",
11         "alternate_name": "",
12         "display_name": "N/A",
13         "id": "",
14         "type": "user"
15     },
16     "authentication": {
17         "credential_provider": "NFC",
18         "issuer": "6FC02554"
19     },
20     "event": {
21         "display_message": "Access Denied / Unknown (NFC)",
22         "published": 1689077487000,
23         "reason": "",
24         "result": "BLOCKED",
25         "type": "access.door.unlock"
26     },
27     "target": [
28         {
29             "alternate_id": "",
30             "alternate_name": "",
31             "display_name": "UA-HUB-3855",
32             "id": "7483c2773855",
33             "type": "UAH"
34         }
35     ],
36     "tag": "access"
37 }
38 ]
39 ]
40 },
41 "page": 1,
42 "total": 4
43 }
```