


Keine Seiten

### Administration

 [Einstellungen](#) >

 [Things](#) >

 [Model](#)

 [Items](#)

 [Pages](#)

 [Rules](#)

 [Scripts](#)

 [Schedule](#)

 [Entwickler Tools](#) >

 [Über & Hilfe](#) >

Status: OFFLINE 

### COMMUNICATION\_ERROR

Error with read:

```
org.openhab.core.io.transport.modbus.exception.ModbusConnectionE
```

```
Error connecting to endpoint
```

```
ModbusSerialSlaveEndpoint@3e67ae[portName=/dev/ttyAMA0]
```

Identifier modbus:poller:ab28005056

Label Regular Poll Raumtemperatur IST

Location e.g. Kitchen

Parent Bridge

Bridge [Modbus Serial Slave](#) >

## Information

Thing Type

Regular Poll

## Configuration

Show advanced

Poll Interval

2000

Poll interval in milliseconds. Use zero to disable automatic polling.

Start

202

Address of the first register, coil, or discrete input to poll.

Input as zero-based index number, e.g. in place of 400001 (first holding register), use the address 0.

Length

2

**Required** Number of registers, coils or discrete inputs to read.

Maximum number of registers is 125 while 2000 is maximum for coils and discrete inputs.

Type



openhabian

<http://192.168.1.91:8080>